

Flow-Sync™ فير صت ل راع شت س إ م اظن

ة ن ا ز ي م ي ا س ا ن ت ف ي ر ص ت ل ل ق ي ق د ة ب ق ا ر م

ة ي س ا س ا ل ا ت ا ز ي م ا

- ACC و I-Core م ك ح ت ت ا ح و ل ع م ط ب ر ل ل ن ي ك ل س ة ط ا س ب ب (ر ت م 300 / م د ق 1000 ح)
- (في ر ص ت ل ا ن ع ت ا م و ل ع م ب م ك ح ت ل ا ة ح و ل ي ذ غ ي ن ي ز خ ت و ة ع ب ا ت م ل ك ل ذ و ، ر ت ل ل ا و ا ن و ل ا ج ا ب ف ي ر ص ت ل ا ت ا ن ا ي ب)
- ت ا ل ص و ع م م د خ ت س ي (ا م ل ل م و ا ق م و ع ي ن ص ت ل ا ي و ق ر ظ ن ا ، ب و ب ن ا ل ر ط ق ل ة ب س ا ن م ل ا ي ت ل ك ش ت ا ذ FCT ل و د ج ل)
- في ر ص ت ل ا ت ا ل د ع م ي و ت س م ة ا ر ق ب ة ط ح م ل ا د و ز ي في ر ص ت ل ا ل ا و ح ا ل ة ج ر د ي ن د ا و ي ل ع ا ع م ل م ا ع ت ل ل ك ل ذ و ر س ك ل ا و ب ي ر س ت ل ا و ر ا ر ض ا ل ا ن م ة ي ا م ح ل ا ي ل ع د ع ا س ي ف ب ي ب ا ن ا ل ا م ا ظ ن ي
- ل ط ر 220 ل ي ل 0 : ه ب ي ص و م ل ا ي ل ا ت م ل ا ط غ ض ل ا ة ب ر م ة ص و ب
- ة ب ر م ة ص و ب / ل ط ر 0.13 > : ط غ ض ل ا ن ا د ق ف ل د ع م
- و ا 18 AWG ة ر د ق ، ر ش ا ب م ل ا ن ف د ل ل 2 x : ك ا ل س ا ل ا م ك ح ت ل ا ة ح و ل ن م ر ت م 300 ح ، ة ب ي ط ق ل ا ة ف ر ع م ل ة م ل ع م و ا ن ا و ل ا ب ة ز م ر م ، ي ل ع ا



Flow-Sync Flow Range

Flow-Sync Diameter	Operating range (l/min)	
	Minimum	Suggested Maximum*
25 mm	7.6	64
40 mm	19	132
50 mm	37.8	208
80 mm	106	454
100 mm	129	738

Notes:

* Good design practice dictates the maximum flow not to exceed 1.5 m/sec. Suggested maximum flow is based upon Class 200 IPS plastic pipe

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/ar/irrigation-product/sensors/nzam-astshar-altstryf-tm-flow-sync>
122324