

HCC

Bring the power of Hydrowise® to residential, commercial, and public-sector projects with this affordable powerhouse.

ةيساسأل تازيملا

- Number of stations: Conventional: 8 to 38 (plastic), 8 to 54 (metal and pedestals)* With two-wire EZDS: up to 54 (all enclosure options)
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- 24-hour maximum station run time provides flexibility for low-flow zones
- Any 2 programs or stations can operate simultaneously, providing more efficient watering
- 2 sensor inputs available for use with any Klik sensors and HC Flow Meter
- 1 P/MV output for pump start relay and master valve activation
- Wi-Fi enabled for quick connection to Hydrowise software
- 8 cm full-colour touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts



OPERATING SPECIFICATIONS

- Transformer input: 120/230 VAC
- Transformer output (24 VAC): 1.4 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.56 A
- 2.4 GHz (only) Wi-Fi router compatible, 802.11 b/g/n 20 MHz
- Supported security protocols: WPA/WPA2 Personal and Enterprise, TLS
- Approvals: Plastic Wall Mount IP55, Plastic Pedestal IP24, NEMA 3R, UL, cUL, FCC, CE, UKCA, RCM
- Warranty period: 5 years

USER-INSTALLED OPTIONS

- Rain-Klik™ for rain sensor shut down

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/ar/irrigation-product/hydrowise/hcc122324>