

## Eco-Rotator

This compact sprinkler offers maximum efficiency, flexibility, and performance.



- Automatic matched precipitation for simplified irrigation design and flexibility
- High distribution uniformity for a healthy landscape and maximum water efficiency
- Double-pop feature protects the nozzle from external debris
- Large inlet filter screen protects the nozzle from internal debris in the system
- Heavy-duty spring for consistent riser retraction



### Operating Specifications

- Low precipitation rate
- Radius range: 1.8 to 9.1 m
- Operational pressure range: 1.7 to 3.8 bar; 170 to 380 kPa
- Recommended operating pressure: 2.8 bar; 280 kPa
- Warranty period: 2 years

### User-Installed Option

- Drain Check Valve: 10 cm model (up to 2 m of elevation) P/N: 462237SP

---

#### ECO ROTATOR PERFORMANCE DATA

---

##### **MP1000**

---

**Radius:** 2.5 to 4.6 m

Adjustable Arc & Full Circle

**Maroon:** 90° to 210°

**Olive:** 360°

| Arc  | Pressure |     | Radius | Flow |       | Precip mm/hr |     |
|------|----------|-----|--------|------|-------|--------------|-----|
|      | bar      | kPa |        | m    | m³/hr | l/min        | ■   |
| 90°  | 1.7      | 170 | 4.0    | ...  | ...   | ...          | ... |
|      | 2.0      | 200 |        | 3.7  | 0.04  | 0.61         | 11  |
|      | 2.5      | 250 |        | 4.0  | 0.04  | 0.68         | 10  |
|      | 2.8      | 280 |        | 4.1  | 0.04  | 0.70         | 10  |
|      | 3.0      | 300 |        | 4.3  | 0.04  | 0.73         | 10  |
|      | 3.5      | 350 |        | 4.4  | 0.05  | 0.78         | 10  |
|      | 3.8      | 380 |        | 4.6  | 0.05  | 0.81         | 9   |
| 180° | 1.7      | 170 | 4.0    | ...  | ...   | ...          | ... |
|      | 2.0      | 200 |        | 3.7  | 0.07  | 1.20         | 11  |
|      | 2.5      | 250 |        | 4.0  | 0.08  | 1.35         | 10  |
|      | 2.8      | 280 |        | 4.1  | 0.08  | 1.40         | 10  |
|      | 3.0      | 300 |        | 4.3  | 0.09  | 1.46         | 10  |
|      | 3.5      | 350 |        | 4.4  | 0.09  | 1.56         | 10  |
|      | 3.8      | 380 |        | 4.6  | 0.10  | 1.62         | 9   |
| 210° | 1.7      | 170 | 4.0    | ...  | ...   | ...          | ... |
|      | 2.0      | 200 |        | 3.7  | 0.09  | 1.41         | 11  |
|      | 2.5      | 250 |        | 4.0  | 0.10  | 1.58         | 10  |
|      | 2.8      | 280 |        | 4.1  | 0.10  | 1.63         | 10  |
|      | 3.0      | 300 |        | 4.3  | 0.10  | 1.71         | 10  |
|      | 3.5      | 350 |        | 4.4  | 0.11  | 1.82         | 10  |
|      | 3.8      | 380 |        | 4.6  | 0.11  | 1.89         | 9   |
| 360° | 1.7      | 170 | 4.0    | ...  | ...   | ...          | ... |
|      | 2.0      | 200 |        | 3.5  | 0.14  | 2.40         | 12  |
|      | 2.5      | 250 |        | 4.0  | 0.16  | 2.69         | 10  |
|      | 2.8      | 280 |        | 4.1  | 0.17  | 2.81         | 10  |
|      | 3.0      | 300 |        | 4.3  | 0.18  | 2.94         | 10  |
|      | 3.5      | 350 |        | 4.4  | 0.19  | 3.17         | 10  |
|      | 3.8      | 380 |        | 4.5  | 0.20  | 3.25         | 10  |

## MP2000

---

**Radius:** 4 to 6.4 m

Adjustable Arc & Full Circle

**Black:** 90° to 210°

**Red:** 360°

| Arc  | Pressure |     | Radius | Flow |       | Precip mm/hr |    |
|------|----------|-----|--------|------|-------|--------------|----|
|      | bar      | kPa |        | m    | m³/hr | l/min        | ■  |
| 90°  | 1.7      | 170 | 5.2    | 5.2  | 0.07  | 1.18         | 11 |
|      | 2.0      | 200 |        | 5.5  | 0.07  | 1.23         | 10 |
|      | 2.5      | 250 |        | 5.8  | 0.09  | 1.43         | 10 |
|      | 2.8      | 280 |        | 6.1  | 0.09  | 1.52         | 10 |
|      | 3.0      | 300 |        | 6.4  | 0.09  | 1.57         | 9  |
|      | 3.5      | 350 |        | 6.7  | 0.10  | 1.68         | 9  |
|      | 3.8      | 380 |        | 6.7  | 0.11  | 1.77         | 9  |
| 180° | 1.7      | 170 | 4.9    | 4.9  | 0.13  | 2.22         | 11 |
|      | 2.0      | 200 |        | 5.2  | 0.14  | 2.35         | 11 |
|      | 2.5      | 250 |        | 5.5  | 0.16  | 2.67         | 11 |
|      | 2.8      | 280 |        | 5.8  | 0.17  | 2.80         | 10 |
|      | 3.0      | 300 |        | 6.1  | 0.17  | 2.90         | 10 |
|      | 3.5      | 350 |        | 6.4  | 0.19  | 3.15         | 9  |
|      | 3.8      | 380 |        | 6.4  | 0.19  | 3.22         | 9  |
| 210° | 1.7      | 170 | 4.9    | 4.9  | 0.16  | 2.58         | 11 |
|      | 2.0      | 200 |        | 5.2  | 0.17  | 2.75         | 11 |
|      | 2.5      | 250 |        | 5.5  | 0.19  | 3.08         | 10 |
|      | 2.8      | 280 |        | 5.8  | 0.20  | 3.25         | 10 |
|      | 3.0      | 300 |        | 6.1  | 0.21  | 3.42         | 10 |
|      | 3.5      | 350 |        | 6.4  | 0.22  | 3.70         | 9  |
|      | 3.8      | 380 |        | 6.4  | 0.23  | 3.80         | 10 |
| 360° | 1.7      | 170 | 4.9    | 4.9  | 0.27  | 4.42         | 11 |
|      | 2.0      | 200 |        | 5.2  | 0.28  | 4.72         | 11 |
|      | 2.5      | 250 |        | 5.5  | 0.32  | 5.28         | 10 |
|      | 2.8      | 280 |        | 5.8  | 0.33  | 5.55         | 10 |
|      | 3.0      | 300 |        | 6.1  | 0.35  | 5.80         | 10 |
|      | 3.5      | 350 |        | 6.4  | 0.37  | 6.25         | 9  |
|      | 3.8      | 380 |        | 6.4  | 0.38  | 6.40         | 9  |

#### MP3000


---

**Radius:** 6.7 to 9.1 m

Adjustable Arc & Full Circle

**Blue:** 90° to 210°

**Grey:** 360°

| Arc  | Pressure |     | Radius  | Flow |       | Precip mm hr |   |    |
|--|----------|-----|---|------|-------|--------------|---|----|
|  | bar      | kPa |   | m    | m³/hr | l/min        |  |    |
| 90°     | 1.7      | 170 |   | 7.6  | 0.16  | 2.63         | 11  | 13 |
|  | 2.0      | 200 |   | 8.2  | 0.17  | 2.77         | 10  | 11 |
|  | 2.5      | 250 |   | 8.5  | 0.19  | 3.08         | 10  | 12 |
|  | 2.8      | 280 |   | 9.1  | 0.20  | 3.25         | 9   | 11 |
|  | 3.0      | 300 |   | 9.1  | 0.20  | 3.38         | 10  | 11 |
|  | 3.5      | 350 |   | 9.1  | 0.22  | 3.67         | 11  | 12 |
|  | 3.8      | 380 |   | 9.1  | 0.23  | 3.80         | 11  | 13 |
| 180°    | 1.7      | 170 |   | 7.6  | 0.32  | 5.48         | 11  | 13 |
|  | 2.0      | 200 |   | 8.2  | 0.35  | 5.88         | 10  | 12 |
|  | 2.5      | 250 |   | 8.5  | 0.40  | 6.55         | 11  | 12 |
|  | 2.8      | 280 |   | 9.1  | 0.41  | 6.88         | 10  | 11 |
|  | 3.0      | 300 |   | 9.1  | 0.43  | 7.18         | 10  | 12 |
|  | 3.5      | 350 |   | 9.1  | 0.47  | 7.77         | 11  | 13 |
|  | 3.8      | 380 |   | 9.1  | 0.45  | 8.02         | 12  | 13 |
| 210°    | 1.7      | 170 |   | 7.6  | 0.38  | 6.40         | 11  | 13 |
|  | 2.0      | 200 |   | 8.2  | 0.41  | 6.85         | 10  | 12 |
|  | 2.5      | 250 |   | 8.5  | 0.46  | 7.65         | 11  | 12 |
|  | 2.8      | 280 |   | 9.1  | 0.48  | 8.02         | 10  | 11 |
|  | 3.0      | 300 |   | 9.1  | 0.50  | 8.37         | 10  | 12 |
|  | 3.5      | 350 |   | 9.1  | 0.54  | 9.03         | 11  | 13 |
|  | 3.8      | 380 |   | 9.1  | 0.56  | 9.37         | 12  | 13 |
| 360°  | 1.7      | 170 |  | 7.6  | 0.66  | 10.98        | 11  | 13 |
|  | 2.0      | 200 |   | 8.2  | 0.70  | 11.72        | 10  | 12 |
|  | 2.5      | 250 |   | 8.5  | 0.79  | 13.10        | 11  | 12 |
|  | 2.8      | 280 |   | 9.1  | 0.83  | 13.75        | 10  | 11 |
|  | 3.0      | 300 |   | 9.1  | 0.87  | 14.37        | 10  | 12 |
|  | 3.5      | 350 |   | 9.1  | 0.93  | 15.52        | 11  | 13 |
|  | 3.8      | 380 |   | 9.1  | 0.96  | 16.07        | 12  | 13 |

**Bold** = Recommended pressure

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/cn/irrigation-product/mp-rotator/eco-rotator>

122324