





10A-HE

3.0

0° 360°

25°





	bar		kPa		m		mm/h	
	100	150	200	250	300	350	400	450
90° 	1.0	100	2.7	0.08	1.36	45	52	
	1.5	150	2.8	0.09	1.55	48	55	
	2.1	210	3.0	0.10	1.67	44	51	
	2.5	250	3.1	0.11	1.82	45	52	
	3.0	300	3.2	0.12	1.93	45	52	
180° 	1.0	100	2.7	0.16	2.65	44	50	
	1.5	150	2.8	0.18	2.94	45	52	
	2.1	210	3.0	0.19	3.24	43	50	
	2.5	250	3.1	0.21	3.52	44	51	
	3.0	300	3.2	0.23	3.79	44	51	
270° 	1.0	100	2.7	0.24	3.97	44	50	
	1.5	150	2.8	0.26	4.41	45	52	
	2.1	210	3.0	0.29	4.85	43	50	
	2.5	250	3.1	0.32	5.28	44	51	
	3.0	300	3.2	0.34	5.68	44	51	
360° 	1.0	100	2.7	0.32	5.30	44	50	
	1.5	150	2.8	0.35	5.88	45	52	
	2.1	210	3.0	0.39	6.47	43	50	
	2.5	250	3.1	0.42	7.04	44	51	
	3.0	300	3.2	0.45	7.57	44	51	

12A-HE

3.0

0° 360°

25°





						mm/h	
	bar	kPa	m			■	▲
90° 	1.0	100	3.3	0.12	2.01	44	51
	1.5	150	3.5	0.13	2.23	44	51
	2.1	210	3.7	0.14	2.38	42	48
	2.5	250	3.8	0.16	2.65	44	51
	3.0	300	3.9	0.17	2.84	45	51
180° 	1.0	100	3.3	0.23	3.88	43	49
	1.5	150	3.5	0.125	4.24	42	48
	2.1	210	3.7	0.28	4.62	40	47
	2.5	250	3.8	0.30	5.03	42	48
	3.0	300	3.9	0.33	5.53	42	50
270° 	1.0	100	3.3	0.35	5.82	43	49
	1.5	150	3.5	0.38	6.36	42	48
	2.1	210	3.7	0.42	6.93	40	47
	2.5	250	3.8	0.45	7.55	42	48
	3.0	300	3.9	0.50	8.29	44	50
360° 	1.0	100	3.3	0.47	7.76	43	49
	1.5	150	3.5	0.51	8.48	42	48
	2.1	210	3.7	0.55	9.24	40	47
	2.5	250	3.8	0.60	10.07	42	48
	3.0	300	3.9	0.66	11.05	44	50

15A-HE

4.8

0° 360°

25°

						mm/h	
	bar	kPa	m			■	▲
90° 	1.0	100	4.2	0.18	2.95	40	46
	1.5	150	4.4	0.20	3.33	41	48
	2.1	210	4.6	0.22	3.63	41	48
	2.5	250	4.7	0.24	4.05	44	51
	3.0	300	4.8	0.26	4.28	45	51
180° 	1.0	100	4.2	0.35	5.78	39	45
	1.5	150	4.4	0.38	6.38	40	46
	2.1	210	4.6	0.42	7.08	40	46
	2.5	250	4.7	0.47	7.76	42	49
	3.0	300	4.8	0.50	8.39	44	50
270° 	1.0	100	4.2	0.52	8.67	39	45
	1.5	150	4.4	0.57	9.58	40	46
	2.1	210	4.6	0.64	10.62	40	46
	2.5	250	4.7	0.70	11.64	42	49
	3.0	300	4.8	0.75	12.59	42	50
360° 	1.0	100	4.2	0.69	11.56	39	45
	1.5	150	4.4	0.77	12.77	40	46
	2.1	210	4.6	0.85	14.16	40	46
	2.5	250	4.7	0.93	15.52	42	49
	3.0	300	4.8	1.01	16.78	44	50

17A-HE

4.6

0° 360°

25°

	bar	kPa	m			mm/h
90°	1.0	100	4.6	0.22	3.61	41 47
	1.5	150	4.8	0.24	4.04	42 49
	2.1	210	5.2	0.28	4.69	42 48
	2.5	250	5.3	0.29	4.90	42 48
	3.0	300	5.4	0.31	5.25	43 50
180°	1.0	100	4.6	0.40	6.68	38 44
	1.5	150	4.8	0.46	7.70	40 46
	2.1	210	5.2	0.54	8.93	40 46
	2.5	250	5.3	0.56	9.33	40 46
	3.0	300	5.4	0.50	10.02	41 48
270°	1.0	100	4.6	0.60	10.02	38 44
	1.5	150	4.8	0.69	11.55	40 46
	2.1	210	5.2	0.80	13.40	40 46
	2.5	250	5.3	0.84	14.00	40 46
	3.0	300	5.4	0.90	15.05	41 48
360°	1.0	100	4.6	0.80	13.36	38 44
	1.5	150	4.8	0.92	15.40	40 46
	2.1	210	5.2	1.07	17.87	40 46
	2.5	250	5.3	1.12	18.66	40 46
	3.0	300	5.4	1.29	20.06	41 48

mm/h

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/cn/irrigation-product/pro-gaoxiaopenzui>
122324