

# ST-1200-BR

ST-1200-BR

- 5
- 12
- 10 18
- 22.5°
- 
- 
- 
- 40° 360°
- 

- 20.4 35.1
- 6.13 29.76 102.1 495.9
- 2.0 6.0 bar 200 600 KPa

- 1.5 40 x 1.5 40 BSP P/N 241401SP



## ST-1200BR NOZZLE PERFORMANCE DATA

Nozzle	Pressure PSI	Radius ft.	Flow GPM	Precip in/hr	
				■	▲
10 • Black	30	67	27.0	1.16	1.34
	45	75	32.8	1.12	1.30
	60	85	38.1	1.02	1.17
	75	90	43.5	1.03	1.19
12 • Black	30	68	33.6	1.40	1.62
	45	78	41.2	1.30	1.51
	60	88	47.6	1.18	1.37
	75	98	53.1	1.06	1.23
14 • Black	30	70	45.7	1.80	2.07
	45	86	56.0	1.46	1.68
	60	100	64.7	1.25	1.44
	75	110	72.5	1.15	1.33
16 • Black	30	72	59.5	2.21	2.55
	45	93	73.0	1.62	1.88
	60	103	84.3	1.53	1.77
	75	116	80.9	1.16	1.34
18 • Black	30	95	92.5	1.97	2.28
	45	104	107.0	1.90	2.20
	60	111	119.5	1.87	2.16
	75	115	131.0	1.91	2.20

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/cn/irrigation-product/stxitong/st-1200-br-122324>