

HDL

Hunter HDL-CV HDL-PC HDL-R

-
-
-
-
-
-
- (HDL-R)
-
- (CV-ND)
-
- (CV)
-
-

- 2.1 3.4 l/hr
- 30 cm 45 cm 60 cm
- 16.76 mm x 14.22 mm
- (HDL-BLNK)

- 1 4.2 bar; 100 420 kPa
- 120 125
- 5 2

- HDL-09-12-250-COP
- HDL-09-12-1K-COP
- HDL-06-12-250-COP
- HDL-06-12-1K-COP

[\(PDF\)](#)



HDL 17 MM Pressure-Compensating and Reclaimed - Minimum Operating Pressure of 0.7 bar

HDL-PC and HDL-R - 1.5 L/hr

HDL-PC and HDL-R - 2.1 L/hr

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	87	123	156
1.0	30	45	60
2.0	125	177	224
1.0	72	101	129
3.0	149	210	266
2.0	103	147	186
4.0	167	235	299
3.0	123	174	220
4.0	137	194	247

HDL 17 MM Check Valve - Minimum Operating Pressure of 1 bar**HDL-CV - 2.5 L/hr**

Pressure (bar)	Emitter Spacing (cm)		
	30	45	60
1.0	62	88	112
2.0	106	163	207
3.0	142	200	250
4.0	184	288	289

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/cn/irrigation-product/micro-irrigation/hdl122324>