

Eco-Rotator

This compact sprinkler offers maximum efficiency, flexibility, and performance.

HAUPTVORTEILE

- Automatic matched precipitation for simplified irrigation design and flexibility
- High distribution uniformity for a healthy landscape and maximum water efficiency
- Double-pop feature protects the nozzle from external debris
- Large inlet filter screen protects the nozzle from internal debris in the system
- Heavy-duty spring for consistent riser retraction

Operating Specifications

- Low precipitation rate
- Radius range: 1.8 to 9.1 m
- Operational pressure range: 1.7 to 3.8 bar; 170 to 380 kPa
- Recommended operating pressure: 2.8 bar; 280 kPa
- Warranty period: 2 years

User-Installed Option

- Drain Check Valve: 10 cm model (up to 2 m of elevation) P/N: 462237SP







MP1000

Wurfweite: 2,5 bis 4,5 m

Einstellbarer Teilkreis

Kastanienbraun: 90° - 210°

Oliv: 360°

Teilkreis	Druck		Wurfweite	Durchfluss		Niederschl. mm/Std	
	Bar	kPa		m ³ /Std	l/min	■	▲
90° 	1,7	170
	2,0	200	3,7	0,04	0,61	11	12
	2,5	250	4,0	0,04	0,68	10	12
	2,8	280	4,1	0,04	0,70	10	11
	3,0	300	4,3	0,04	0,73	10	11
	3,5	350	4,4	0,05	0,78	10	11
	3,8	380	4,6	0,05	0,81	9	11
180° 	1,7	170
	2,0	200	3,7	0,07	1,20	11	12
	2,5	250	4,0	0,08	1,35	10	12
	2,8	280	4,1	0,08	1,40	10	11
	3,0	300	4,3	0,09	1,46	10	11
	3,5	350	4,4	0,09	1,56	10	11
	3,8	380	4,6	0,10	1,62	9	11
210° 	1,7	170
	2,0	200	3,7	0,09	1,41	11	13
	2,5	250	4,0	0,10	1,58	10	12
	2,8	280	4,1	0,10	1,63	10	11
	3,0	300	4,3	0,10	1,71	10	11
	3,5	350	4,4	0,11	1,82	10	11
	3,8	380	4,6	0,11	1,89	9	11
360° 	1,7	170
	2,0	200	3,5	0,14	2,40	12	14
	2,5	250	4,0	0,16	2,69	10	12
	2,8	280	4,1	0,17	2,81	10	12
	3,0	300	4,3	0,18	2,94	10	11
	3,5	350	4,4	0,19	3,17	10	11
	3,8	380	4,5	0,20	3,25	10	11





MP2000

Wurfweite: 4 bis 6,4 m

Einstellbarer Teilkreis

Schwarz: 90° - 210°

Rot: 360°

Teilkreis	Druck		Wurfweite	Durchfluss		Niederschl. mm/Std	
	Bar	kPa		m ³ /Std	l/min	■	▲
90° 	1,7	170	5,2	0,07	1,18	11	12
	2,0	200	5,5	0,07	1,23	10	11
	2,5	250	5,8	0,09	1,43	10	12
	2,8	280	6,1	0,09	1,52	10	11
	3,0	300	6,4	0,09	1,57	9	11
	3,5	350	6,7	0,10	1,68	9	10
	3,8	380	6,7	0,11	1,77	9	11
180° 	1,7	170	4,9	0,13	2,22	11	12
	2,0	200	5,2	0,14	2,35	11	12
	2,5	250	5,5	0,16	2,67	11	12
	2,8	280	5,8	0,17	2,80	10	12
	3,0	300	6,1	0,17	2,90	10	11
	3,5	350	6,4	0,19	3,15	9	10
	3,8	380	6,4	0,19	3,22	9	11
210° 	1,7	170	4,9	0,16	2,58	11	12
	2,0	200	5,2	0,17	2,75	11	13
	2,5	250	5,5	0,19	3,08	10	12
	2,8	280	5,8	0,20	3,25	10	12
	3,0	300	6,1	0,21	3,42	10	11
	3,5	350	6,4	0,22	3,70	9	10
	3,8	380	6,4	0,23	3,80	10	11
360° 	1,7	170	4,9	0,27	4,42	11	12
	2,0	200	5,2	0,28	4,72	11	13
	2,5	250	5,5	0,32	5,28	10	12
	2,8	280	5,8	0,33	5,55	10	12
	3,0	300	6,1	0,35	5,80	10	11
	3,5	350	6,4	0,37	6,25	9	10
	3,8	380	6,4	0,38	6,40	9	10





MP3000

Wurfweite: 6,7 bis 9,1 m

Einstellbarer Teilkreis

Blau: 90° - 210°

Grau: 360°

Teilkreis	Druck		Wurfweite	Durchfluss		Niederschl. mm/Std	
	Bar	kPa		m ³ /Std	l/min	■	▲
90° 	1,7	170	7,6	0,16	2,63	11	13
	2,0	200	8,2	0,17	2,77	10	11
	2,5	250	8,5	0,19	3,08	10	12
	2,8	280	9,1	0,20	3,25	9	11
	3,0	300	9,1	0,20	3,38	10	11
	3,5	350	9,1	0,22	3,67	11	12
	3,8	380	9,1	0,23	3,80	11	13
180° 	1,7	170	7,6	0,32	5,48	11	13
	2,0	200	8,2	0,35	5,88	10	12
	2,5	250	8,5	0,40	6,55	11	12
	2,8	280	9,1	0,41	6,88	10	11
	3,0	300	9,1	0,43	7,18	10	12
	3,5	350	9,1	0,47	7,77	11	13
	3,8	380	9,1	0,45	8,02	12	13
210° 	1,7	170	7,6	0,38	6,40	11	13
	2,0	200	8,2	0,41	6,85	10	12
	2,5	250	8,5	0,46	7,65	11	12
	2,8	280	9,1	0,48	8,02	10	11
	3,0	300	9,1	0,50	8,37	10	12
	3,5	350	9,1	0,54	9,03	11	13
	3,8	380	9,1	0,56	9,37	12	13
360° 	1,7	170	7,6	0,66	10,98	11	13
	2,0	200	8,2	0,70	11,72	10	12
	2,5	250	8,5	0,79	13,10	11	12
	2,8	280	9,1	0,83	13,75	10	11
	3,0	300	9,1	0,87	14,37	10	12
	3,5	350	9,1	0,93	15,52	11	13
	3,8	380	9,1	0,96	16,07	12	13

Optimale Düsenleistung wird in Fettschrift dargestellt.

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/de/irrigation-product/mp-rotator/eco-rotator>
122324