

## Eco-Indicator

Confirm system operation and adequate pressure with this handy visual tool.

### KEY BENEFITS

- Visible bright yellow or reclaimed purple riser stem and cap indicate when system is in operation
- Stem pops up when pressure exceeds the threshold and assists in confirming low pressures if not raised
- Connects via bottom or side inlet ports for easy installation; side inlet port is available on 30 cm version

### OPERATING SPECIFICATIONS

- ECO-ID:
  - Operating pressure: up to 5 bar; 500kPa
  - Indication of system operation: above 0.8 bar; 80kPa
  - Warranty period: 2 years
- ECO-ID-12/ECO-ID-12-R:
  - Operating pressure: up to 7 bar; 700kPa
  - Indication of system operation: above 1 bar; 100kPa
  - Warranty period: 5 years



### USER-INSTALLED OPTIONS (FOR 30 CM ECO-INDICATOR)

- Drain check valve (up to 3 m of elevation: P/N 437400SP)
- SJ Swing Joint: SJ-512 (½" threaded x 30 cm length)

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/en-metric/irrigation-product/micro-irrigation/eco-indicator>  
122324