

MP Rotator™ Strip Nozzle

MP Rotator Strip Nozzles offer a high-efficiency solution for irrigating narrow spaces.

KEY BENEFITS

- Low precipitation rate prevents runoff
- Match the precipitation rate of MP Strip Nozzles to either Standard MP Rotator Nozzles or MP800 Nozzles, depending on the layout of the space
- Double-pop feature protects the nozzle from external debris
- Wind-resistant streams improve uniformity and prevent misting
- Removable filter screen prevents nozzle from clogging
- Colour-coded for easy identification

OPERATING SPECIFICATIONS




- Recommended operating pressure: 2.8 bar; 280 kPa
- Minimum radius setting achieved at 2.1 bar; 210 kPa
- Warranty period: 3 years

OPTIONS

- Pair with Pro-Spray™ PRS40 pop-up for pressure regulation to 2.8 bar; 280 kPa for nominal radius settings
- Pair with Pro-Spray PRS30 pop-up for pressure regulation to 2.1 bar; 210 kPa for minimum radius settings



MP ROTATOR PERFORMANCE DATA SIDE STRIPS

MP-LCS-515: Ivory, MP Left Corner Strip MP-RCS-515: Copper, MP Right Corner Strip MP-SS-530 Brown, MP Side Strip								
Arc	Pressure		Radius	Flow		Precip. mm/hr		
	bar	kPa		m ³ /hr	l/min	■	▲	
Left Strip 	2.1	210	1.2 x 4.2	0.04	0.64	31	15	
	2.5	250	1.4 x 4.4	0.04	0.68	27	13	
	2.8	280	1.5 x 4.5	0.04	0.72	26	13	
	3.0	300	1.6 x 4.6	0.05	0.79	26	13	
	3.5	350	1.7 x 4.7	0.05	0.87	26	13	
	3.8	380	1.8 x 4.8	0.05	0.91	25	13	
Right Strip 	2.1	210	1.2 x 4.2	0.04	0.64	31	15	
	2.5	250	1.4 x 4.4	0.04	0.68	27	13	
	2.8	280	1.5 x 4.5	0.04	0.72	26	13	
	3.0	300	1.6 x 4.6	0.05	0.79	26	13	
	3.5	350	1.7 x 4.7	0.05	0.87	26	13	
	3.8	380	1.8 x 4.8	0.05	0.91	25	13	
Side Strip 	2.1	210	1.2 x 8.4	0.07	1.25	30	15	
	2.5	250	1.4 x 8.7	0.08	1.36	27	13	
	2.8	280	1.5 x 9.0	0.09	1.44	26	13	
	3.0	300	1.6 x 9.3	0.09	1.55	25	13	
	3.5	350	1.7 x 9.6	0.10	1.67	24	12	
	3.8	380	1.8 x 9.9	0.11	1.79	24	12	

Bold = Recommended pressure

Note: Strip pattern radius can be adjusted by 25%. MP Rotator is designed to maintain matched precipitation after radius adjustment. To match the precipitation rate of Standard MP Rotator models, use single-row or triangular spacing. To match the precipitation rate of MP Rotator MP800 Nozzles, use rectangular spacing.

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/en-metric/irrigation-product/mp-rotator/mp-rotatortm-strip-nozzle>
122324