## **ICD Decoders**

Hunter's premium two-wire decoders for long-distance, high-station-count ACC2 applications include two-way communications and integrated surge protection.

## **KEY BENEFITS**

- ICD Decoders are compatible with ACC2 Decoder Controllers and legacy ACC-99D Decoder Controllers
- 1-, 2-, 4-, and 6-station versions provide maximum flexibility
- Sensor decoders allow Flow and Clik Sensor monitoring via the two-wire paths
- Field-programmable decoders accept station numbers directly, and do not require entering serial numbers into the control panel
- Decoders can be programmed before installation at the controller interface
- Use of the ICD-HP Programmer allows for wireless decoder programming or reprogramming after installation to the two-wire path
- Integrated surge protection eliminates the need for extra surge protection devices
- Colour-coded wiring connections simplify installation
- Industrial-grade, waterproof DBRY-6 Splice Connectors included for two-wire path splices



- Maximum recommended distance, decoder to solenoid: 45 m
- Maximum distance to decoder via two-wire path:
  - ∘ 2 mm<sup>2</sup> wire path: 3 km
  - $\circ$  3.3 mm<sup>2</sup> wire path: 4.5 km
- Approvals: UL, cUL, FCC, CE, UKCA, RCM
- Decoder rating: IP68 (submersible)
- Warranty period: 5 years

## USER-INSTALLED OPTIONS

- Wireless handheld ICD-HP Programmer
- DECSTAKE10 Universal Decoder Stake, 10-pack

| ID WIRE MAXIMUM WIRE RUNS         |                                   |  |  |  |
|-----------------------------------|-----------------------------------|--|--|--|
| ID 1 Wire                         | ID 2 Wire                         |  |  |  |
| 1,500 m with legacy DUAL™ systems | 2,300 m with legacy DUAL™ systems |  |  |  |
| 3 km with ICD systems             | 4.5 km with ICD systems           |  |  |  |

| ID WIRE MODEL GUIDE                |             |   |             |  |
|------------------------------------|-------------|---|-------------|--|
| 2 mm <sup>2</sup><br>Decoder Cable |             | 3.3 mm <sup>2</sup> Long-Range,<br>Heavy-Duty Decoder Cable |             |  |
| ID1GRY                             | Gray jacket | ID2GRY  | Gray jacket |  |



| ID WIRE MODEL GUIDE                |               |        |   |  |  |
|------------------------------------|---------------|--------|---|--|--|
| 2 mm <sup>2</sup><br>Decoder Cable |               | I      | 3.3 mm <sup>2</sup> Long-Range,<br>Heavy-Duty Decoder Cable |  |  |
| ID1PUR                             | Purple jacket | ID2PUR | Purple jacket   |  |  |
| ID1YLW                             | Yellow jacket | ID2YLW | Yellow jacket   |  |  |
| ID10RG                             | Orange jacket | ID2ORG | Orange jacket   |  |  |
| ID1BLU                             | Blue jacket   | ID2BLU | Blue jacket   |  |  |
| ID1TAN                             | Tan jacket    | ID2TAN | Tan jacket  |  |  |
|                                    |               |        |   |  |  |
|                                    |               |        |   |  |  |
|                                    |               |        |   |  |  |
|                                    |               |        |   |  |  |
|                                    |               |        |   |  |  |

Copyright © 2025 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

https://www.hunterirrigation.com/en-metric/irrigation-product/controllers/icd-decoders 011025