

HC

The cost-effective solution for residential projects, the HC Controller provides smart water savings and remote irrigation management capabilities.

KEY BENEFITS

- Number of stations: 6 or 12 (fixed indoor)
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- 24-hour maximum station run time provides flexibility for low-flow zones
- 2 sensor inputs available for use with any Klik sensors and HC Flow Meter
- Station outputs can also be used to activate a pump start relay or master valve
- Wi-Fi enabled for quick connection to Hydrawise software
- 7 cm full-colour touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts (12-station model only)



ELECTRICAL SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- 2.4 GHz (only) Wi-Fi router compatible, 802.11 b/g/n 20 MHz
- Supported security protocols: WPA/WPA2 Personal and Enterprise, TLS
- Approvals: UL, cUL, FCC, CE, UKCA, RCM
- Warranty period: 2 years

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/en-metric/irrigation-product/hydrawise/hc-122324>