

1" PGV

Highly versatile, robust irrigation valves for simple installation and serviceability. 100% of Hunter valves are water-tested.

KEY BENEFITS

- External/internal manual bleed allows for quick and easy activation at the valve
- Double-beaded diaphragm seal design ensures leak-free performance
- Captive bonnet screws eliminate the possibility of lost parts during disassembly
- Triple-tool bonnet screws are compatible with standard or Phillips screwdrivers as well as a nut driver
- Encapsulated solenoid with captive plunger used on every Hunter valve provides hassle-free service
- Flow control maximises efficiency and prolongs the life of the system



User-Installed Options

- Accu Sync™ pressure regulation at the valve*
- DC-latching solenoid for battery-powered controllers (P/N 458200)
- Solenoid conduit cover (P/N 464322)

Factory-Installed Options

- LS: Valve without solenoid
- DC: DC-latching solenoid for battery-powered controllers

1" (25 mm) PGV Operating Specifications

- Flow: 0.05 to 9 m³ /hr; 0.7 to 150 l/min
- Recommended pressure range: 1.5 to 10 bar; 150 to 1,000 kPa
- Temperature rating: 66°C
- Warranty period: 2 years

1½" (40 mm) and 2" (50 mm) PGV Operating Specifications

- Flow:
 - PGV-151: 5 to 27 m³ /hr; 75 to 450 l/min
 - PGV-201: 5 to 34 m³ /hr; 75 to 570 l/min
- Recommended pressure range: 1.5 to 10 bar; 150 to 1000 kPa
- Temperature rating: 66°C
- Warranty period: 2 years
- View more details for [1½" and 2" PGV >](#)

1" (25 mm) PGV Pressure Loss

1" (25 mm) PGV Pressure Loss in Bar

Flow m ³ /hr	Pressure Loss bar
0.3	0.08
1.0	0.11
2.5	0.13
3.5	0.16
4.5	0.23
5.5	0.43
6.5	0.62
8.0	1.10
9.0	1.48

1" (25 mm) PGV Pressure Loss in KPa

Flow l/min	Pressure Loss kPa
4	8
20	11
40	13
55	16
75	23
95	43
115	62
135	110
150	148

1½" (40 mm) and 2" (50 mm) PGV Pressure Loss

PGV Pressure Loss in Bar				
Flow m ³ /hr	1½" (40 mm) Globe	1½" (40 mm) Angle	2" (50 mm) Globe	2" (50 mm) Angle
4.5	0.2	0.2	0.1	0.1
5.5	0.2	0.2	0.1	0.1
6.5	0.2	0.2	0.1	0.1
8.0	0.2	0.2	0.1	0.1
9.0	0.2	0.2	0.1	0.1
11.0	0.3	0.2	0.1	0.1
13.5	0.3	0.3	0.1	0.1
18.0	0.4	0.4	0.2	0.1
22.5	0.6	0.5	0.3	0.2
27.0	0.8	0.8	0.4	0.3
30.5			0.6	0.5
34.0			0.7	0.6

PGV Pressure Loss in kPa

Flow l/min	1½" (40 mm) Globe	1½" (40 mm) Angle	2" (50 mm) Globe	2" (50 mm) Angle
75	20	22	4	9
95	20	21	5.5	9
115	21	21	7.5	9.5
135	22	21	9	10
150	25	23	12	11
200	27	24	14	12
325	47	41	26	19
400	65	59	33	24
500	96	92	43	32
625			56	45
775			74	64

Solenoid Specifications

- 24 VAC solenoid
 - 350 mA inrush, 190 mA holding, 60 Hz
 - 370 mA inrush, 210 mA holding, 50 Hz

1" (25 MM) PGV VALVE

Flow m ³ /hr	Pressure Loss bar
0.3	0.08
1.0	0.11
2.5	0.13
3.5	0.16
4.5	0.23
5.5	0.43
6.5	0.62
8.0	1.10
9.0	1.48

1" (25 MM) PGV VALVE

Flow l/min	Pressure Loss kPa
4	8
20	11
40	13
55	16
75	23
95	43
115	62
135	110
150	148

PGV PRESSURE LOSS IN BAR

Flow m ³ /hr	1½" (40 mm)		2" (50 mm)	
	Globe	Angle	Globe	Angle
4.5	0.2	0.2	0.1	0.1
5.5	0.2	0.2	0.1	0.1
6.5	0.2	0.2	0.1	0.1
8.0	0.2	0.2	0.1	0.1
9.0	0.2	0.2	0.1	0.1
11.0	0.3	0.2	0.1	0.1
13.5	0.3	0.3	0.1	0.1
18.0	0.4	0.4	0.2	0.1
22.5	0.6	0.5	0.3	0.2
27.0	0.8	0.8	0.4	0.3
30.5			0.6	0.5
34.0			0.7	0.6

PGV PRESSURE LOSS IN KPA

Flow l/min	1½" (40 mm)		2" (50 mm)	
	Globe	Angle	Globe	Angle
75	20	22	4	9
95	20	21	5.5	9
115	21	21	7.5	9.5
135	22	21	9	10
150	25	23	12	11
200	27	24	14	12
325	47	41	26	19
400	65	59	33	24
500	96	92	43	32
625			56	45
775			74	64

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/en-metric/irrigation-product/valves/1-pgv-122324>