

## Eco-Rotator

This compact sprinkler offers maximum efficiency, flexibility, and performance.

### VANTAGGI PRINCIPALI

- Automatic matched precipitation for simplified irrigation design and flexibility
- High distribution uniformity for a healthy landscape and maximum water efficiency
- Double-pop feature protects the nozzle from external debris
- Large inlet filter screen protects the nozzle from internal debris in the system
- Heavy-duty spring for consistent riser retraction

### Operating Specifications

- Low precipitation rate
- Radius range: 1.8 to 9.1 m
- Operational pressure range: 1.7 to 3.8 bar; 170 to 380 kPa
- Recommended operating pressure: 2.8 bar; 280 kPa
- Warranty period: 2 years

### User-Installed Option

- Drain Check Valve: 10 cm model (up to 2 m of elevation) P/N: 462237SP



---

### DATI DELLE PRESTAZIONI DI ECO ROTATOR

---

#### MP1000





---

**Raggio:** 2,5 - 4,6 m

Regolabile Arco

**Ruggine:** 90° to 210°

**Verde oliva:** 360°

Arco	Pressione		Raggio	Portata		Precip. mm/ora	
	bar	kPa		m <sup>3</sup> /ora	l/min	■	▲
90° 	1,7	170	...	...	...	...	...
	2,0	200	3,7	0,04	0,61	11	12
	2,5	250	4,0	0,04	0,68	10	12
	2,8	280	4,1	0,04	0,70	10	11
	3,0	300	4,3	0,04	0,73	10	11
	3,5	350	4,4	0,05	0,78	10	11
	3,8	380	4,6	0,05	0,81	9	11
180° 	1,7	170	...	...	...	...	...
	2,0	200	3,7	0,07	1,20	11	12
	2,5	250	4,0	0,08	1,35	10	12
	2,8	280	4,1	0,08	1,40	10	11
	3,0	300	4,3	0,09	1,46	10	11
	3,5	350	4,4	0,09	1,56	10	11
	3,8	380	4,6	0,10	1,62	9	11
210° 	1,7	170	...	...	...	...	...
	2,0	200	3,7	0,09	1,41	11	13
	2,5	250	4,0	0,10	1,58	10	12
	2,8	280	4,1	0,10	1,63	10	11
	3,0	300	4,3	0,10	1,71	10	11
	3,5	350	4,4	0,11	1,82	10	11
	3,8	380	4,6	0,11	1,89	9	11
360° 	1,7	170	...	...	...	...	...
	2,0	200	3,5	0,14	2,40	12	14
	2,5	250	4,0	0,16	2,69	10	12
	2,8	280	4,1	0,17	2,81	10	12
	3,0	300	4,3	0,18	2,94	10	11
	3,5	350	4,4	0,19	3,17	10	11
	3,8	380	4,5	0,20	3,25	10	11





**MP2000**

**Raggio:** 4 - 6,4 m

Regolabile Arco

**Nero:** 90° - 210°

**Rosso:** 360°

Arco	Pressione		Raggio	Portata		Precip. mm/ora	
	bar	kPa		m <sup>3</sup> /ora	l/min	■	▲
90° 	1,7	170	5,2	0,07	1,18	11	12
	2,0	200	5,5	0,07	1,23	10	11
	2,5	250	5,8	0,09	1,43	10	12
	2,8	280	6,1	0,09	1,52	10	11
	3,0	300	6,4	0,09	1,57	9	11
	3,5	350	6,7	0,10	1,68	9	10
	3,8	380	6,7	0,11	1,77	9	11
180° 	1,7	170	4,9	0,13	2,22	11	12
	2,0	200	5,2	0,14	2,35	11	12
	2,5	250	5,5	0,16	2,67	11	12
	2,8	280	5,8	0,17	2,80	10	12
	3,0	300	6,1	0,17	2,90	10	11
	3,5	350	6,4	0,19	3,15	9	10
	3,8	380	6,4	0,19	3,22	9	11
210° 	1,7	170	4,9	0,16	2,58	11	12
	2,0	200	5,2	0,17	2,75	11	13
	2,5	250	5,5	0,19	3,08	10	12
	2,8	280	5,8	0,20	3,25	10	12
	3,0	300	6,1	0,21	3,42	10	11
	3,5	350	6,4	0,22	3,70	9	10
	3,8	380	6,4	0,23	3,80	10	11
360° 	1,7	170	4,9	0,27	4,42	11	12
	2,0	200	5,2	0,28	4,72	11	13
	2,5	250	5,5	0,32	5,28	10	12
	2,8	280	5,8	0,33	5,55	10	12
	3,0	300	6,1	0,35	5,80	10	11
	3,5	350	6,4	0,37	6,25	9	10
	3,8	380	6,4	0,38	6,40	9	10






**MP3000**

**Raggio:** 6,7 - 9,1

Regolabile Arco

**Blu:** 90° to 210°

**Grigio:** 360°

Arco	Pressione			Raggio	Portata		Precip. mm/ora	
	bar	kPa			m	m³/ora	l/min	■
90° 	1,7	170		7,6	0,16	2,63	11	13
	2,0	200		8,2	0,17	2,77	10	11
	2,5	250		8,5	0,19	3,08	10	12
	2,8	280		9,1	0,20	3,25	9	11
	3,0	300		9,1	0,20	3,38	10	11
	3,5	350		9,1	0,22	3,67	11	12
	3,8	380		9,1	0,23	3,80	11	13
180° 	1,7	170		7,6	0,32	5,48	11	13
	2,0	200		8,2	0,35	5,88	10	12
	2,5	250		8,5	0,40	6,55	11	12
	2,8	280		9,1	0,41	6,88	10	11
	3,0	300		9,1	0,43	7,18	10	12
	3,5	350		9,1	0,47	7,77	11	13
	3,8	380		9,1	0,45	8,02	12	13
210° 	1,7	170		7,6	0,38	6,40	11	13
	2,0	200		8,2	0,41	6,85	10	12
	2,5	250		8,5	0,46	7,65	11	12
	2,8	280		9,1	0,48	8,02	10	11
	3,0	300		9,1	0,50	8,37	10	12
	3,5	350		9,1	0,54	9,03	11	13
	3,8	380		9,1	0,56	9,37	12	13
360° 	1,7	170	7,6	0,66	10,98	11	13	
	2,0	200	8,2	0,70	11,72	10	12	
	2,5	250	8,5	0,79	13,10	11	12	
	2,8	280	9,1	0,83	13,75	10	11	
	3,0	300	9,1	0,87	14,37	10	12	
	3,5	350	9,1	0,93	15,52	11	13	
	3,8	380	9,1	0,96	16,07	12	13	

**Neretto** = Prestazione ottimale della testina.

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/it/irrigation-product/mp-rotator/eco-rotator>  
122324