

Eco-Rotator

This compact sprinkler offers maximum efficiency, flexibility, and performance.

KLUCZOWE KORZYŚCI

- Automatic matched precipitation for simplified irrigation design and flexibility
- High distribution uniformity for a healthy landscape and maximum water efficiency
- Double-pop feature protects the nozzle from external debris
- Large inlet filter screen protects the nozzle from internal debris in the system
- Heavy-duty spring for consistent riser retraction

Operating Specifications

- Low precipitation rate
- Radius range: 1.8 to 9.1 m
- Operational pressure range: 1.7 to 3.8 bar; 170 to 380 kPa
- Recommended operating pressure: 2.8 bar; 280 kPa
- Warranty period: 2 years





User-Installed Option

- Drain Check Valve: 10 cm model (up to 2 m of elevation) P/N: 462237SP







MP1000

Promień: 2,5 do 4,6 m
Regulowany zakres i pełny zakres
Bordowy: 90° - 210°
Oliwkowy: 360°

Kąt zraszania	Ciśnienie		Promień	Przepływ		Opad mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
90° 	1,7	170
	2,0	200	3,7	0,04	0,61	11	12
	2,5	250	4,0	0,04	0,68	10	12
	2,8	280	4,1	0,04	0,70	10	11
	3,0	300	4,3	0,04	0,73	10	11
	3,5	350	4,4	0,05	0,78	10	11
	3,8	380	4,6	0,05	0,81	9	11
180° 	1,7	170
	2,0	200	3,7	0,07	1,20	11	12
	2,5	250	4,0	0,08	1,35	10	12
	2,8	280	4,1	0,08	1,40	10	11
	3,0	300	4,3	0,09	1,46	10	11
	3,5	350	4,4	0,09	1,56	10	11
	3,8	380	4,6	0,10	1,62	9	11
210° 	1,7	170
	2,0	200	3,7	0,09	1,41	11	13
	2,5	250	4,0	0,10	1,58	10	12
	2,8	280	4,1	0,10	1,63	10	11
	3,0	300	4,3	0,10	1,71	10	11
	3,5	350	4,4	0,11	1,82	10	11
	3,8	380	4,6	0,11	1,89	9	11
360° 	1,7	170
	2,0	200	3,5	0,14	2,40	12	14
	2,5	250	4,0	0,16	2,69	10	12
	2,8	280	4,1	0,17	2,81	10	12
	3,0	300	4,3	0,18	2,94	10	11
	3,5	350	4,4	0,19	3,17	10	11
	3,8	380	4,5	0,20	3,25	10	11

MP2000

Promień: 4 do 6,4 m
Regulowany zakres i pełny zakres
Czarny: 90° - 210°
Czerwony: 360°

Kąt zraszania	Ciśnienie		Promień	Przepływ		Opad mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
90° 	1,7	170	5,2	0,07	1,18	11	12
	2,0	200	5,5	0,07	1,23	10	11
	2,5	250	5,8	0,09	1,43	10	12
	2,8	280	6,1	0,09	1,52	10	11
	3,0	300	6,4	0,09	1,57	9	11
	3,5	350	6,7	0,10	1,68	9	10
	3,8	380	6,7	0,11	1,77	9	11
180° 	1,7	170	4,9	0,13	2,22	11	12
	2,0	200	5,2	0,14	2,35	11	12
	2,5	250	5,5	0,16	2,67	11	12
	2,8	280	5,8	0,17	2,80	10	12
	3,0	300	6,1	0,17	2,90	10	11
	3,5	350	6,4	0,19	3,15	9	10
	3,8	380	6,4	0,19	3,22	9	11
210° 	1,7	170	4,9	0,16	2,58	11	12
	2,0	200	5,2	0,17	2,75	11	13
	2,5	250	5,5	0,19	3,08	10	12
	2,8	280	5,8	0,20	3,25	10	12
	3,0	300	6,1	0,21	3,42	10	11
	3,5	350	6,4	0,22	3,70	9	10
	3,8	380	6,4	0,23	3,80	10	11
360° 	1,7	170	4,9	0,27	4,42	11	12
	2,0	200	5,2	0,28	4,72	11	13
	2,5	250	5,5	0,32	5,28	10	12
	2,8	280	5,8	0,33	5,55	10	12
	3,0	300	6,1	0,35	5,80	10	11
	3,5	350	6,4	0,37	6,25	9	10
	3,8	380	6,4	0,38	6,40	9	10





MP3000

Promień: 6,7 do 9,1 m

Regulowany zakres i pełny zakres

Niebieski: 90° - 210°

Szary: 360°

Kąt zraszania	Ciśnienie		Promień	Przepływ		Opad mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
90° 	1,7	170	7,6	0,16	2,63	11	13
	2,0	200	8,2	0,17	2,77	10	11
	2,5	250	8,5	0,19	3,08	10	12
	2,8	280	9,1	0,20	3,25	9	11
	3,0	300	9,1	0,20	3,38	10	11
	3,5	350	9,1	0,22	3,67	11	12
	3,8	380	9,1	0,23	3,80	11	13
180° 	1,7	170	7,6	0,32	5,48	11	13
	2,0	200	8,2	0,35	5,88	10	12
	2,5	250	8,5	0,40	6,55	11	12
	2,8	280	9,1	0,41	6,88	10	11
	3,0	300	9,1	0,43	7,18	10	12
	3,5	350	9,1	0,47	7,77	11	13
	3,8	380	9,1	0,45	8,02	12	13
210° 	1,7	170	7,6	0,38	6,40	11	13
	2,0	200	8,2	0,41	6,85	10	12
	2,5	250	8,5	0,46	7,65	11	12
	2,8	280	9,1	0,48	8,02	10	11
	3,0	300	9,1	0,50	8,37	10	12
	3,5	350	9,1	0,54	9,03	11	13
	3,8	380	9,1	0,56	9,37	12	13
360° 	1,7	170	7,6	0,66	10,98	11	13
	2,0	200	8,2	0,70	11,72	10	12
	2,5	250	8,5	0,79	13,10	11	12
	2,8	280	9,1	0,83	13,75	10	11
	3,0	300	9,1	0,87	14,37	10	12
	3,5	350	9,1	0,93	15,52	11	13
	3,8	380	9,1	0,96	16,07	12	13

Tłusty druk = zalecane ciśnienie

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/pl/irrigation-product/mp-rotator/eco-rotator>
122324