

G-995

Covering 75' to 104', the G-995 is the perfect combination of performance and reliability.

KLUCZOWE KORZYŚCI

- G-995 is an adjustable part-circle model (40° to 360°)
- Higher-flow, longer-radius rotor designed for single-row systems
- Contour back-nozzle capability for special applications

MODEL SPECIFICATIONS

- Adjustable Arc (40° to 360°)

MODEL VARIATIONS

C = Check-O-Matic checks up to 25' in elevation change and readily converts to Normally Open Hydraulic with through the top connections.

D = Decoder Valve-In-Head with all "E" specifications below.

DD = 2-Station Decoder Valve-In-Head with all "E" specifications below.

E = Electric Valve-In-Head with adjustable pressure regulation, on-off-auto selector, 190mA (350mA inrush) solenoid with captive plunger and internal downstream bleed.

OPERATING SPECIFICATIONS

- Discharge rate: 29.5 to 83.8 GPM
- Radius: 75' to 104'
- Pressure range: 80 to 120 PSI
- Pressure rating: 150 PSI





G995

| | |
|-----------------|--------------------|
| Overall Height | 13-1/4" |
| Pop-up Height | 3" |
| Flange Diameter | 7-1/2" |
| Inlet Size | 1-1/2" Female ACME |

G995 NOZZLE PERFORMANCE DATA*

| Nozzle | Pressure | Radius | Flow | Precip in/hr | |
|-------------------|----------|--------|------|--------------|------|
| | PSI | ft | GPM | ■ | ▲ |
| 25 • Lt. Blue | 80 | 75 | 29.5 | 0.50 | 0.58 |
| | 90 | 76 | 31.5 | 0.52 | 0.61 |
| | 100 | 77 | 33.2 | 0.54 | 0.62 |
| | 110 | 78 | 35.6 | 0.56 | 0.65 |
| | 120 | 79 | 37.5 | 0.58 | 0.67 |
| 33 • Grey | 80 | 77 | 36.2 | 0.59 | 0.68 |
| | 90 | 78 | 38.2 | 0.60 | 0.70 |
| | 100 | 79 | 40.4 | 0.62 | 0.72 |
| | 110 | 81 | 42.6 | 0.62 | 0.72 |
| | 120 | 82 | 44.8 | 0.64 | 0.74 |
| 38 • Red | 80 | 80 | 40.6 | 0.61 | 0.71 |
| | 90 | 82 | 43.0 | 0.62 | 0.71 |
| | 100 | 84 | 45.4 | 0.62 | 0.72 |
| | 110 | 85 | 47.6 | 0.63 | 0.73 |
| | 120 | 86 | 50.0 | 0.65 | 0.75 |
| 43 • Dk. Brown | 80 | 84 | 46.1 | 0.63 | 0.73 |
| | 90 | 85 | 48.5 | 0.65 | 0.75 |
| | 100 | 85 | 50.7 | 0.68 | 0.78 |
| | 110 | 86 | 53.4 | 0.69 | 0.80 |
| | 120 | 87 | 55.7 | 0.71 | 0.82 |
| 48 • Dk. Green | 80 | 88 | 50.2 | 0.62 | 0.72 |
| | 90 | 89 | 52.6 | 0.64 | 0.74 |
| | 100 | 90 | 55.1 | 0.65 | 0.76 |
| | 110 | 92 | 57.5 | 0.65 | 0.76 |
| | 120 | 92 | 60.5 | 0.69 | 0.79 |
| 53 • Dk. Blue | 80 | 91 | 54.9 | 0.64 | 0.74 |
| | 90 | 91 | 57.2 | 0.66 | 0.77 |
| | 100 | 92 | 59.5 | 0.68 | 0.78 |
| | 110 | 93 | 62.1 | 0.69 | 0.80 |
| | 120 | 92 | 64.4 | 0.73 | 0.85 |
| 63 • Black | 80 | 93 | 62.3 | 0.69 | 0.80 |
| | 90 | 94 | 65.5 | 0.71 | 0.82 |
| | 100 | 95 | 69.0 | 0.74 | 0.85 |
| | 110 | 96 | 71.9 | 0.75 | 0.87 |
| | 120 | 98 | 74.7 | 0.75 | 0.86 |
| 73 • Orange | 80 | 96 | 72.7 | 0.76 | 0.88 |
| | 90 | 98 | 75.4 | 0.76 | 0.87 |
| | 100 | 100 | 78.1 | 0.75 | 0.87 |
| | 110 | 102 | 80.9 | 0.75 | 0.86 |
| | 120 | 104 | 83.8 | 0.75 | 0.86 |

Note: *Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral.

** For low angle nozzle performance, reduce radius by 15%

Copyright © 2025 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterirrigation.com/pl/node/26191>

010925