# **HC Flow Meter**

Detect, monitor, and report critical flow zone data and total system flows with this robust and simple-to-install flow sensor. Add wireless flow-monitoring capabilities to Hydrawise® Systems with a simple and affordable communication kit.

### **KEY BENEFITS**

- Compatible with HC, HPC, Pro-HC, and HCC Controllers
- Compatible with ICC2 Controller via Centralus™ communication modules
- Flow Rate: 0.22 to 132 GPM (depending on size)
- Provides station-level flow rates and totals in Hydrawise Software
- Sends automatic alerts in the event of high-flow, low-flow, or unscheduled flow conditions
- Flow reports within Hydrawise Software can display total system water use and individual station water use for accurate water budgeting and tracking
- Robust brass construction with union fittings for easy installation and removal for winterization
- Analog dial on the face of the meter displays daily flow totals and a leak detector
- Optional wireless communication kit available for use with any HC Flow Meter and Hydrawise-enabled HC, HPC, Pro-HC, or HCC Controllers



| HC-075-FLOW (¾") HC   | IC-100-FLOW (1")       | HC-150-FLOW<br>(1½")   | HC-200-FLOW (2")          |
|---|------------------------|------------------------|---------------------------|
| Minimum flow (GPM) 0.22 0.3                                   | .3                     | 0.88                   | 1.98                      |
| Maximum recommended flow (GPM) 15 30                          | 0                      | 66                     | 105                       |
| Maximum flow rate (GPM) 21 34                                 | 4                      | 88                     | 132                       |
| Dial reading (U.S. gal)  1 pulse per 0.1 U.S. 1 gal  gal  gal | pulse per 1 U.S.<br>al | 1 pulse per 1 U.S. gal | 1 pulse per 1 U.S.<br>gal |
| Max working pressure (PSI) 230 23                             | 30                     | 230                    | 230                       |

#### **Operating Specifications**

- Scaled pulse output is precalibrated from the factory based on the size of the meter
- When wired directly to the controller, meter must be installed with shielded, minimum 18 AWG wire, up to 1,000' from the controller
- Accuracy: ± 2% of reading at recommended flow
- Warranty period: 2 years

#### Wireless Operating Specifications

- 500' range (line of sight) from transmitter to receiver
- Communication frequency: 900 MHz for use in North America
- Transmitter power supply: 3 AA batteries
- Receiver power supply: 24 VAC from host controller



## **Approvals**

- FCC, CE, and RCM approved
- Transmitter is IP68 rated
- Receiver is IP24 rated

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

https://hunterirrigation.com/irrigation-product/sensors/hc-flow-meter 122324