


## Pro-Spray® PRS40

To optimize MP Rotator® performance, the Pro-Spray PRS40 is pressure-regulated to 40 PSI.

### KEY BENEFITS

- Industry's strongest spray body for years of reliable performance
- Pressure-regulated to 40 PSI for the MP Rotator
- Gray cap for easy field identification
- Co-molded wiper seal made from chemical- and chlorine-resistant materials
- Innovative seal design prevents cap-to-body leaks, even with a loose cap
- Heavy-duty spring for consistent riser retraction
- Check valve option eliminates low-head drainage
- FloGuard™ Technology option eliminates water waste in the event of a missing nozzle
- Interchangeable components for easier servicing, retrofits, and upgrades



### Operating Specifications

- Recommended pressure range: 15 to 100 PSI
- Warranty period: 5 years

### Factory-Installed Options

- Check valve available for 4", 6", and 12" models (up to 14' of elevation)
- Reclaimed water identification
- FloGuard™ Technology available for check valve models

### User-Installed Options

- Drain Check Valve P/N: 437400SP
  - Up to 14' of elevation for 4", 6", and 12" models
  - Up to 10' of elevation for 3" model
- Reclaimed water ID cap P/N: 458562SP
- Snap-on reclaimed cover P/N: PROS-RC-CAP-SP
- Shutoff cap P/N: 213600SP
- Shutoff nozzle P/N: 916400SP

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/irrigation-product/spray-bodies/pro-sprayr-prs40>  
122324