

ACCU SYNC® PRESSURE REGULATOR

These robust solutions provide a simple way to achieve unparalleled pressure regulation for optimal performance.

OPERATING SPECIFICATIONS

- Regulation from 20 to 100 PSI
- Static pressure: 150 PSI
- Required dynamic pressure differential: 15 PSI
- Works with AC and DC-Latching Solenoids
- Works with any Hunter valve
- Warranty period: 2 years

ACCU SYNC VALVE RECOMMENDED FLOW RANGE

Valve	Flow GPM
PGV-100/101	15 to 40
PGV-151	20 to 120
PGV-201	40 to 150
ICV-101	15 to 40
ICV-151	20 to 150
ICV-201	40 to 200
ICV-301	150 to 300
IBV-101	15 to 40
IBV-151	20 to 150
IBV-201	40 to 200
IBV-301	150 to 300

ACCU SYNC APPLICATIONS

- **Adjustable 20-100 PSI** For full customization, the adjustable Accu Sync can regulate pressure from 20 to 100 PSI

ACCU SYNC PRESSURE REGULATOR – SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Inlet/Outlet
ACCU SYNC	ADJ = Adjustable Pressure Regulator (20-100 PSI)

Example:
ICV-201G-B-AS-ADJ = 2" ICV globe valve with flow control, user-installed adjustable Accu Sync Pressure Regulator

ADJUSTABLE



**ACCUSYNC-ADJ
PRESSURE REGULATOR**
Height with solenoid: 3¼"

ADAPTER



SOLENOID ADAPTER



AC Solenoid

P/N 606800: Includes one red (common) and one red (station) wire