

HCC

Bring the power of Hydrowise™ Software to residential, commercial, and public-sector projects with this affordable powerhouse.

Try Hydrowise Software today at hydrowise.com.

KEY BENEFITS

- Number of stations:
 - Conventional: 8 to 38 (plastic), 8 to 54 (metal and pedestals)
 - Up to 54 stations (all enclosure options) with two-wire EZ Decoder System and/or Wireless Valve Links
- Any 2 programs or stations can operate simultaneously to improve irrigation efficiency
- 2 sensor inputs available for use with any Klik Sensors and HC Flow Meter
- 1 P/MV output for pump start relay and master valve activation
- 8 cm full-colour touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts

OPERATING SPECIFICATIONS

- Transformer input: 120/230 VAC
- Transformer output (24 VAC): 1.4 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.56 A
- Run a maximum of 4 Hunter solenoids 1.04 A at once
- 2.4 GHz (only) Wi-Fi router compatible, 802.11 b/g/n 20 MHz
- Supported security protocols: WPA/WPA2 Personal (only), TLS
- Approvals: Plastic Wall Mount IP55 (outdoor), Plastic Pedestal IP24, Metal wall-mounted enclosure IP55 (outdoor), Metal Pedestal IP55 (outdoor), UL, cUL, FCC, CE, UKCA, RCM, ISED
- Warranty period: 2 years

USER-INSTALLED OPTIONS

- Wireless HC Flow Meter option permits wireless flow monitoring for Hydrowise-enabled systems
- Compatible with ROAM and ROAM XL Remotes

HCC	
Model	Description
HCC-800-PL	8-station base model, plastic outdoor, wall mount
HCC-800-M	8-station base model, grey metal outdoor, wall mount
HCC-800-SS	8-station base model, stainless steel, wall mount
HCC-800-PP	8-station base model, plastic pedestal
HCC-FPUP	Retrofit upgrade kit for ICC and ICC2 Controllers
ICC-PED	Grey pedestal for metal wall-mount cabinet
ICC-PED-SS	Stainless steel pedestal for stainless steel wall mount
ICC-PWB	Optional pedestal wiring board for metal pedestals
ANT-EXT-KIT	Universal antenna extension kit

HCC SERIES STATION EXPANSION	
Model	Description
ICM-400	4-station plug-in module with enhanced surge protection
ICM-800	8-station plug-in module with enhanced surge protection
ICM-2200	22-station expansion module (maximum one per controller)
EZDS	See hunter.info/EZDSem
WVOM-E	See hunter.info/WVLEm



Plastic
Height: 30.5 cm
Width: 35 cm
Depth: 12.7 cm


Metal
(grey or stainless)
Height: 40.6 cm
Width: 33 cm
Depth: 12.7 cm




Metal Pedestal
(metal/stainless)
Height: 91.4 cm
Width: 29.2 cm
Depth: 12.7 cm

Plastic Pedestal
Height: 99 cm
Width: 61 cm
Depth: 43 cm

Compatible with:



HC Flow Meter



EZ Decoder System



Wireless Valve Link



Smart Drop
Recognised as a responsible water-saving tool