



- 01 **Rugged:** Automatic arc return and non-strippable drive prevent damage from vandalism
- 02 **Versatile:** Part- and full-circle in one model, from 50° to 360°, adds system flexibility
- 03 **Efficient:** Built-in check valve saves water and reduces liability

I-25 ROTOR

This Rugged Rotor Delivers Top Performance in Commercial Applications

The I-25 gets the job done with power, efficiency, and commercial-grade reliability. With a robust watering radius of 11.9 to 21.6 m, this rotor can be used in a variety of applications and environments. The compact, highly durable design is available in a plastic model or stainless steel for tough-as-nails strength. With a 5-year warranty, the I-25 also has options for reclaimed water ID and high-speed watering. A standard check valve is built in, and a wide selection of high-performance nozzles is available. Efficient, tough, and built-to-last, Hunter's I-25 rotor works hard day in and day out so you don't have to.

I-25 ROTOR FEATURES & SPECIFICATIONS

Features

- Plastic/stainless steel riser models: 10 cm, 15 cm
- Arc settings: 50° to 360°
- Factory-installed rubber cover
- Through-the-top arc adjustment
- QuickCheck™ arc mechanism
- Water-lubricated gear drive
- Nozzle choices: 11
- Nozzle range: #4 to #28
- Warranty period: 5 years

Specifications

- Radius: 11.9 to 21.6 m
- Flow rate: 0.82 to 7.24 m³/hr; 13.6 to 120.7 l/min
- Recommended pressure range: 2.5 to 7.0 bar; 250 to 700 kPa
- Operating pressure range: 2.5 to 7.0 bar; 250 to 700 kPa
- Precipitation rates: 15 mm/hr approx.
- Nozzle trajectory: 25°

Models

I-25-04

Overall height: 20 cm
 Pop-up height: 10 cm
 Exposed diameter: 5 cm
 Inlet size: 1" BSP



I-25-06

Overall height: 26 cm
 Pop-up height: 15 cm
 Exposed diameter: 5 cm
 Inlet size: 1" BSP



I-25 (PLASTIC) - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-25-04 = 10 cm pop-up I-25-06 = 15 cm pop-up	Adjustable arc, plastic riser, check valve, and 5 nozzles	B = BSP inlet threads R = Reclaimed water ID	#4 - #28 = Factory-installed nozzle number

I-25 (STAINLESS STEEL) - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-25-04-SS = 10 cm pop-up I-25-06-SS = 15 cm pop-up	Adjustable arc, stainless steel riser, check valve, and 5 nozzles	B = BSP inlet threads R = Reclaimed water ID HS = High-speed HS-R = High-speed and reclaimed water ID	#4 - #28 = Factory-installed nozzle number

Examples:

I-25-04 - B = 10 cm pop-up, adjustable arc, BSP inlet threads

I-25-04-SS - R - B - 18 = 10 cm pop-up, adjustable arc, stainless steel riser, reclaimed water ID, and #18 nozzle, BSP inlet threads

I-25-06-SS - B = 15 cm pop-up, adjustable arc, stainless steel riser, BSP inlet threads

Website hunterirrigation.com | **Customer Support** +1-760-744-5240 | **Technical Service** +1-760-591-7383

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

Denise Mullikin, President, Landscape Irrigation and Outdoor Lighting