

# AIR/VACUUM RELIEF VALVE

Prevent water hammer and system collapse by discharging air during startup and allowing air to enter during shutdown.

## KEY BENEFITS

- Releases air pockets without premature closure
- Leak-free closure after release
- Helps prevent system collapse through vacuum relief

## PRODUCT SPECIFICATIONS

- UV-protected and corrosion-resistant material

## OPERATING SPECIFICATIONS

- Pressure range: up to 80 PSI
- Warranty period: 2 years



**AVR-075**

Height: 5"  
Width: 2"  
Inlet: 3/4" MPT



**PLD-AVR**

1/2" Air/vacuum relief valve

## Air/Vacuum Relief Valve Installed



# AUTOMATIC FLUSH VALVE

Keep laterals clean by automatically flushing water, air, and debris at each system startup.

## KEY BENEFITS

- Flushes debris automatically at every system startup
- Reversible diaphragm to coordinate with low or high flow
- Lateral placement provides better grit tolerance

## PRODUCT SPECIFICATIONS

- Removable top for diaphragm maintenance

## OPERATING SPECIFICATIONS

- Pressure range: up to 60 PSI
- Low-flow diaphragm side: 2 to 5 GPM
- High-flow diaphragm side: 5 to 12 GPM
- Warranty period: 1 year



**AFV-B**

Automatic flush valve with  
17 mm barb connection



**AFV-T**

Automatic flush valve with  
1/2" MPT connection

## Automatic Flush Valve Installed

