

FILTER REGULATORS

This all-in-one choice features a state-of-the-art Senninger regulator and a stainless steel filter screen.

KEY BENEFITS

- HFR-075 (Hunter filter regulator)
 - Compact, all-in-one filter and regulator minimize required valve box space
 - Senninger regulator provides precise regulation to protect system from high pressure
 - 150 mesh (100 microns) stainless steel screen for years of reliable filtration
 - Wide flow range covers most drip applications
- Warranty period: 2 years



HFR-075-25
HFR-075-40
 Height: 7"
 Width: 2¾"
 Length: 6¼"
 ¾" inlet x ¾" outlet



HFR-100-075-25
HFR-100-075-40
 Height: 7"
 Width: 2¾"
 Length: 6¼"
 1" inlet x ¾" outlet



HFR-100-075-25-R
HFR-100-075-40-R
 Height: 7"
 Width: 2¾"
 Length: 6¼"
 1" inlet x ¾" outlet

HUNTER FILTER REGULATORS

Model	Description
HFR-075-25	¾" inlet x ¾" outlet, regulated at 25 PSI
HFR-075-40	¾" inlet x ¾" outlet, regulated at 40 PSI
HFR-100-075-25	1" inlet x ¾" outlet, regulated at 25 PSI
HFR-100-075-25-R	1" inlet x ¾" outlet, regulated at 25 PSI, reclaimed
HFR-100-075-40	1" inlet x ¾" outlet, regulated at 40 PSI
HFR-100-075-40-R	1" inlet x ¾" outlet, regulated at 40 PSI, reclaimed
133801	Reclaimed filter bonnet

HFR -FILTER REGULATOR KITS

Model	System Flow GPM	Required Pressure for 25 PSI Outlet
HFR-075-25	0.5	30
	2	30
	5	31
	10	33
	15	37
HFR-100-075-25	0.5	30
	2	30
	5	31
	10	32
	15	35
HFR-075-40	0.5	45
	2	45
	5	46
	10	48
	15	54
HFR-100-075-40	0.5	45
	2	45
	5	46
	10	47
	15	52

With standard 150 mesh (100 microns) filter screen