

# G-70 & G-75

These highly efficient block rotors have a powerful gear drive backed by the reliability synonymous with the Hunter name.

## KEY BENEFITS

- G-70B: Full-circle
- G-75B: Full/part-circle (50° to 360°)
- QuickCheck™ arc mechanism (G-70B)
- QuickSet-360 arc mechanism (G-75B)
- Nozzle choices:
  - G-70B: 6 standard trajectory (25°)
  - G-75B: 9 standard trajectory (25°)
- Nozzle range:
  - G-70B: #15 to #28
  - G-75B: #8 to #28
- Exclusive PressurePort™ nozzle technology
- Water-lubricated gear drive
- Check height up to 3 m in elevation change

## OPERATING SPECIFICATIONS

- G-70B
  - Radius: 16.2 to 22.9 m
  - Discharge rate: 2.95 to 7.66 m<sup>3</sup>/hr; 49.2 to 127.6 l/min
  - Pressure range: 3.4 to 6.9 bar; 340 to 690 kPa
- G-75B
  - Radius: 14.3 to 21.6 m
  - Discharge rate: 1.75 to 7.34 m<sup>3</sup>/hr; 29.1 to 122.3 l/m
  - Pressure range: 2.8 to 6.9 bar; 280 to 690 kPa
- All B Series rotors are pressure-rated at 10 bar; 1,000 kPa



### G-70B

Pop-up height: 8 cm  
Overall height: 23 cm  
Flange diameter: 12 cm  
Female inlet: 1/4" (30 mm) Acme



### G-75B

Pop-up height: 8 cm  
Overall height: 23 cm  
Flange diameter: 12 cm  
Female inlet: 1/4" (30 mm) Acme

## G-70B & G-75B - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1	Model	2	Valve Options	3	Nozzle	4	Options
G70	Full-circle	B	Block rotor with check valve	25	Installed G70 nozzle *	S	SSU *
					* Available in SSU model only SSU = #25 (includes nozzle pack)		* Standard stocking unit
G75	Full/part-circle, 50°-360° arc range	B	Block rotor with check valve	25	Installed G75 nozzle **	S	SSU *
					** Available in SSU model only SSU = #25 (includes nozzle pack)		* Standard stocking unit

### Example:

G70-B-25-S = G-70 full-circle block rotor, installed #25 nozzle with nozzle pack, standard stocking unit model

G-70B NOZZLE PERFORMANCE DATA*							
Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m <sup>3</sup> /hr	l/min	■	▲
15 ● Grey	3.4	340	16.2	2.95	49.2	11.3	13.1
	4.1	410	16.5	3.20	53.4	11.8	13.7
	4.5	450	16.8	3.36	56.0	12.0	13.8
	4.8	480	17.1	3.52	58.7	12.1	14.0
	5.5	550	17.7	3.70	61.7	11.8	13.7
18 ● Red	3.4	340	17.7	3.23	53.8	10.3	11.9
	4.1	410	18.0	3.61	60.2	11.2	12.9
	4.5	450	18.3	3.70	61.7	11.1	12.8
	4.8	480	18.3	3.84	64.0	11.5	13.3
	5.5	550	18.6	4.04	67.4	11.7	13.5
20 ● Dk. Brown	3.4	340	18.6	4.27	71.2	12.4	14.3
	4.1	410	18.9	4.45	74.2	12.5	14.4
	4.5	450	19.2	4.66	77.6	12.6	14.6
	4.8	480	19.5	5.00	83.3	13.1	15.2
	5.5	550	19.5	5.32	88.6	14.0	16.1
23 ● Dk. Green	3.4	340	19.2	4.57	76.1	12.4	14.3
	4.1	410	19.8	4.77	79.5	12.2	14.0
	4.5	450	19.8	4.97	82.9	12.7	14.6
	4.8	480	20.1	5.32	88.6	13.1	15.2
	5.5	550	20.4	5.66	94.3	13.6	15.7
25 ● Dk. Blue	3.4	340	19.8	4.95	82.5	12.6	14.6
	4.1	410	20.4	5.11	85.2	12.3	14.1
	4.5	450	20.4	5.36	89.3	12.9	14.8
	4.8	480	21.0	5.75	95.8	13.0	15.0
	5.5	550	21.6	6.11	101.8	13.0	15.1
28 ● Black	4.8	480	21.6	6.38	106.4	13.6	15.7
	5.5	550	21.6	6.79	113.2	14.5	16.7
	6.2	620	22.3	7.22	120.4	14.6	16.8
	6.9	690	22.9	7.66	127.6	14.6	16.9

\* Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral. To calculate precipitation rates for 180° operation, multiply by 2.

G-75B NOZZLE PERFORMANCE DATA*							
Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m <sup>3</sup> /hr	l/min	■	▲
8 ● Lt. Brown	2.8	280	14.3	1.75	29.1	8.5	9.8
	3.4	340	14.9	1.89	31.4	8.5	9.8
	4.1	410	15.2	2.09	34.8	9.0	10.4
	4.5	450	15.2	2.16	36.0	9.3	10.7
	4.8	480	15.5	2.25	37.5	9.3	10.7
10 ● Lt. Green	3.4	340	16.2	2.48	41.3	9.5	11.0
	4.1	410	16.5	2.73	45.4	10.1	11.6
	4.5	450	16.5	2.84	47.3	10.5	12.1
	4.8	480	16.8	2.98	49.6	10.6	12.2
	5.5	550	17.1	3.25	54.1	11.1	12.9
13 ● Lt. Blue	3.4	340	16.8	2.54	42.4	9.1	10.5
	4.1	410	17.1	2.79	46.6	9.6	11.1
	4.5	450	17.1	2.91	48.5	10.0	11.5
	4.8	480	17.4	3.02	50.3	10.0	11.6
	5.5	550	17.4	3.25	54.1	10.8	12.4
15 ● Grey	3.4	340	17.4	3.04	50.7	10.1	11.6
	4.1	410	17.7	3.25	54.1	10.4	12.0
	4.5	450	18.0	3.36	56.0	10.4	12.0
	4.8	480	18.0	3.48	57.9	10.7	12.4
	5.5	550	18.3	3.73	62.1	11.2	12.9
18 ● Red	3.4	340	18.3	3.29	54.9	9.8	11.4
	4.1	410	18.6	3.57	59.4	10.3	11.9
	4.5	450	18.6	3.70	61.7	10.7	12.4
	4.8	480	18.9	3.84	64.0	10.7	12.4
	5.5	550	19.2	4.13	68.9	11.2	12.9
20 ● Dk. Brown	4.1	410	18.9	4.04	67.4	11.3	13.1
	4.5	450	18.9	4.13	68.9	11.6	13.4
	4.8	480	19.2	4.36	72.7	11.8	13.7
	5.5	550	19.5	4.66	77.6	12.2	14.1
	6.2	620	19.8	4.95	82.5	12.6	14.6
23 ● Dk. Green	4.1	410	19.5	4.97	82.9	13.1	15.1
	4.5	450	19.8	4.86	81.0	12.4	14.3
	4.8	480	19.8	5.36	89.3	13.7	15.8
	5.5	550	20.1	5.82	96.9	14.4	16.6
	6.2	620	20.4	6.13	102.2	14.7	17.0
25 ● Dk. Blue	4.1	410	19.8	5.34	89.0	13.6	15.7
	4.5	450	19.8	5.63	93.9	14.4	16.6
	4.8	480	20.4	5.82	96.9	13.9	16.1
	5.5	550	21.0	6.20	103.3	14.0	16.2
	6.2	620	21.6	6.59	109.8	14.1	16.2
28 ● Black	4.8	480	20.1	6.11	101.8	15.1	17.4
	5.5	550	20.7	6.56	109.4	15.3	17.6
	6.2	620	21.3	6.95	115.8	15.3	17.6
	6.9	690	21.6	7.34	122.3	15.7	18.1

### G-70B & G-75B NOZZLES



G-70B



G-75B