

HC

The cost-effective solution for residential projects, the HC Controller provides smart water savings and remote irrigation management capabilities.

KEY BENEFITS

- Number of stations:
 - 6 or 12 (fixed models)
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- 2 sensor inputs available for use with any Clik Sensors and HC Flow Meter
- Station outputs can also be used to activate a pump start relay or master valve
- Wi-Fi enabled for quick connection to Hydrawise Software
- 7 cm full-colour touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts (12-zone models)

OPERATING SPECIFICATIONS

- Transformer input: 230 VAC
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- 2.4 GHz (only) Wi-Fi router compatible, 802.11 b/g/n 20 MHz
- Supported security protocols: WPA/WPA2 Personal (only) TLS, SSL
- Approvals: UL, cUL, FCC, CE, RCM, ISED
- Warranty period: 2 years

USER-INSTALLED OPTIONS


- Wireless HC Flow Meter option permits wireless flow monitoring for Hydrawise-enabled systems

Try Hydrawise Software today at hydrawise.com.




HC
(plastic indoor)
Height: 15.2 cm
Width: 17.8 cm
Depth: 3.3 cm

Compatible with:



HC Flow Meter



Soil-Clik
Sensor



Rain-Clik
Sensor

HC	
Model	Description
HC-601i-E	Fixed 6-station, plastic indoor wall mount, 230 VAC European wall adapter
HC-1201i-E	Fixed 12-station, plastic indoor wall mount, 230 VAC European wall adapter



Smart WaterMark
Recognised as a responsible water-saving tool