

# ICC2

This flexible control system can run any combination of conventional or two-wire outputs with the option to upgrade to cloud-based Centralus™ control.

## KEY BENEFITS

- Number of stations:
  - Conventional: 8 to 38 (plastic), 8 to 54 (metal and pedestals)
  - With two-wire EZDS: up to 54 (all enclosure options)
- 4 independent irrigation programs (8 start times each)
- Any 2 programs can operate simultaneously, providing more efficient watering
- 1 sensor input available for use with Solar Sync® or any Clik sensors
- 1 P/MV output for pump start relay and master valve activation
- Backward compatibility to original ICC Controllers allows for quick updates to older systems
- Upgradeable to Centralus Software for web-based central control options

## OPERATING SPECIFICATIONS

- Transformer input: 120/230 VAC
- Transformer output (24 VAC): 1.4 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.56 A
- Approvals: Wall Mounts IP55 (outdoor), Plastic Pedestal IP24 (outdoor), UL, cUL, FCC, CE, RCM, ISED
- Warranty period: 5 years

## USER-INSTALLED OPTIONS

- WIFIKIT, LANKIT, or CELLKIT communications for cloud-based Centralus control
- Compatible with Flow-Clik® Sensor for catastrophic high-flow shutdown
- Compatible with Solar Sync® Sensor

ICC2	
Model	Description
I2C-800-PL	8-station base model, plastic outdoor wall mount
I2C-800-M	8-station base model, gray metal outdoor, wall mount
I2C-800-SS	8-station base model, stainless steel, wall mount
I2C-800-PP	8-station base model, plastic pedestal
ICC-FPUP2	ICC2 Retrofit Kit for original ICC Controllers
ICC-PED	Gray pedestal for metal controller mount
ICC-PED-SS	Stainless steel pedestal for stainless controller mount
ICC-PWB	Optional pedestal wiring board for metal pedestals

ICC2 SERIES STATION EXPANSION	
Model	Description
ICM-400	4-station plug-in module with enhanced surge suppression
ICM-800	8-station plug-in module with enhanced surge suppression
ICM-2200	22-station expansion module (one per controller)
EZDS	See page 122 for model chart

View Centralus Software today, at [centralus.hunterindustries.com](http://centralus.hunterindustries.com)



**Plastic**  
Height: 12"  
Width: 13¾"  
Depth: 5"

**Metal**  
(gray or stainless steel)  
Height: 16"  
Width: 13"  
Depth: 5"



**Metal Pedestal**  
(gray or stainless steel)  
Height: 36"  
Width: 11½"  
Depth: 5"



**Plastic Pedestal**  
Height: 39"  
Width: 24"  
Depth: 17"

CENTRALUS CONTROLLERS


Compatible with:



**Rain-Clik  
Sensor**



**ROAM Remote  
ROAM XL Remote**



**EZ Decoder  
System**



**EPA WaterSense**  
Add the WaterSense labeled Solar Sync Sensor to improve the water efficiency of this controller.