

# IH RISERS

Simplify point-to-point irrigation with vandal-resistant, heavy-duty IH Risers.

## KEY BENEFITS

- Heavy-duty, military-grade, vandal-resistant design
- Made of flexible PVC for durability
- Brown components blend in with landscape
- Accepts any ½" FPT emitter
- Ideal for slopes
- At-grade or below-grade installation
- Pre-assembled with ½" MPT adapter and specified emitter with check valve
- Available as components for custom assemblies
- Check valve holds back 3.6 m of head

## OPERATING SPECIFICATIONS

- Maximum flow: 26.5 l/min
- Maximum pressure: 4.1 bar; 410 kPa
- Warranty period: 2 years

### IH Risers with Emitters - SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1 Riser Length	2 Emitter Flow with Check Valve Screen	3 Fitting Options
<b>IH-06</b> = 15 cm riser	<b>05-CV</b> = 2 l/hr	<b>(blank)</b> = Brown <b>R</b> = Reclaimed (purple fitting)
<b>IH-12</b> = 30 cm riser	<b>10-CV</b> = 4 l/hr	
<b>IH-18</b> = 45 cm riser	<b>20-CV</b> = 8 l/hr	
<b>IH-24</b> = 60 cm riser	<b>40-CV</b> = 15 l/hr	
<b>IH-36</b> = 90 cm riser	<b>60-CV</b> = 23 l/hr	

#### Example:

**IH-12-10-CV** = 30 cm irrigation hose riser with 4 l/hr emitter with brown fittings

Preassembled IH Risers with Emitters are built to order. Please check with your distributor and/or Hunter Customer Service for lead times.

### IH RISER COMPONENTS SOLD SEPARATELY

Model	Description
<b>SCREEN-CV</b>	Filter screen with 2.7 m check valve
<b>IH-FIT-3850</b>	¾" x ½" MPT IH fitting
<b>IH-FIT-3850-R</b>	¾" x ½" MPT IH fitting (reclaimed)
<b>IH-250</b>	75 m length of irrigation hose
<b>IPS-050-250</b>	75 m length of ½" IPS



IH RISERS



### FACTORY ASSEMBLED IH RISERS

Riser, filter screen, and emitter



#### SCREEN-CV

Filter screen with 3.6 m check valve



#### IH-FIT-3850,

**IH-FIT-3850-R**  
¾" x ½" MPT IH fitting (reclaimed)



#### IPS-050-250

Flexible PVC for creating headers or custom risers



#### IH-250