

IH RISERS

Simplify point-to-point irrigation with vandal-resistant, heavy-duty IH Risers.

KEY BENEFITS

- Heavy-duty, military-grade, vandal-resistant design
- Made of flexible PVC for durability
- Brown components blend in with the landscape
- Purple fittings available for reclaimed water applications
- Accepts any ½" FPT emitter
- Ideal for slope applications
- At-grade or below-grade installation
- Available in multiple lengths for easy assembly
- Available as components for custom lengths

OPERATING SPECIFICATIONS

- Maximum flow: 7 GPM
- Maximum pressure: 60 PSI
- Warranty period: 2 years



IH RISERS

IH Risers – SPECIFICATION BUILDER: ORDER 1 + 2 + 3		
1 Model	2 Riser Length	3 Fitting Options
IH-RISER	06 = 6" riser 12 = 12" riser 18 = 18" riser 24 = 24" riser 36 = 36" riser	(blank) = Brown R = Reclaimed (purple fitting)

Example:
IH-RISER-12 = 12" flexible PVC riser with preglued ½" fittings



SCREEN-CV
Filter screen with 12' check valve



IH-FIT-3850, IH-FIT-3850-R
¾" x ½" MPT IH fitting

MICRO

IH RISER COMPONENTS (SOLD SEPARATELY)	
Model	Description
SCREEN-CV	Filter screen with 12' check valve
IH-FIT-3850	¾" x ½" MPT IH fitting
IH-FIT-3850-R	¾" x ½" MPT IH fitting (reclaimed)
IH-250	250' length of flexible PVC irrigation hose



IH-250
Flexible PVC for creating headers or custom risers

RECOMMENDED GLUES FOR FLEXIBLE PVC

- IPS® Weld-On®:
 - P-68™ primer (recommended for PVC fittings only)
 - P-70™ primer (may be used but P-68 is suggested)
 - 795™ Flex PVC cement
- Christy's®:
 - Purple Primer® or Red Hot Clear Primer® (fittings only)
 - Flex Pro PVC pipe cement
 - Red Hot Blue Glue® (not specialized for flexible PVC)

Compatible with:



Point-Source Emitters



Bubblers



Multi-Port Emitters

IPS, Weld-On, P-68, P-70, and 795 are trademarks of IPS Corporation. Christy's, Purple Primer, Red Hot Clear Primer, and Red Hot Blue Glue are trademarks of T. Christy Enterprises.