

MINI-CLIK™

This sensor halts scheduled irrigation when it detects a preset level of rainfall to prevent water waste.

Sensor: **Rain, Freeze**

KEY BENEFITS

- Shuts off irrigation automatically when the sensor detects rainfall from 3 mm to 19 mm
- Debris-tolerant for reliable operation and no unnecessary shutdowns
- Wireless sensor kit simplifies installation*
- Quick Response™ Technology triggers faster system shutdown for plant protection*
- Built-in freeze sensing halts system operation at 3°C to protect plants and keep roads and walkways ice-free*
- Maintenance-free design with integrated battery for wireless models
- Compatible with most normally open or normally closed irrigation controllers

OPERATING SPECIFICATIONS

- Quick Response Technology* (when enabled):
 - Time to turn off irrigation system: approximately 2 to 5 minutes
 - Time to reset: approximately 4 hours under dry, sunny conditions
 - Time to reset when fully wet: approximately 3 days under dry, sunny conditions
- All models switch rating (24 VAC): 3 A
- Wired models include 7 m of 0.5 mm² sheathed, UL-approved wire
- Wireless model operating frequency: 433 MHz
- Wireless model range is 243 m line of sight from sensor to receiver
- Multiple wireless receivers can be operated from a single wireless sensor
- Approvals: UL, cUL, FCC, CE, UKCA, RCM
- Warranty period: 5 years

USER-INSTALLED OPTIONS

- Optional Gutter Mount for wired models (included with WM-CLIK)
- Vandal-resistant Wireless Sensor Guard for surface- or pole-mounting (order sensor separately)
- Vandal-resistant Wireless Receiver Guard for pedestal mounting (order receiver separately)

*Wireless Mini-Clik Sensor only



Wired Mini-Clik Sensor
(with mounting arm)
Height: 5 cm
Length: 15 cm
Width: 2.5 cm



Wired Mini-Clik Sensor
(with stainless steel enclosure)
Height: 13.9 cm
Length: 7.6 cm
Width: 10.1 cm



Wireless Mini-Clik Sensor
(with mounting arm)
Height: 7.6 cm
Length: 20 cm
Width: 2.5 cm



Wireless Receiver
(with wall-mounting hardware)
Height: 10 cm
Length: 8 cm
Width: 3 cm



Wireless Sensor Guard
(with mounting hardware)
Height: 7 cm
Length: 9.5 cm
Width: 3.2 cm



Wireless Receiver Guard
(with mounting hardware)
Height: 12.7 cm
Length: 10.2 cm
Width: 3.2 cm

MINI-CLIK	
Model	Description
MINI-CLIK	Mini-Clik Sensor
MINI-CLIK-NO	Mini-Clik Sensor, normally open switch
MINI-CLIK-C	Mini-Clik Sensor, conduit mount
SG-MC	Mini-Clik Sensor in a stainless steel sensor enclosure
WM-CLIK	Wireless Mini-Clik Sensor, Receiver, and Gutter Mount
WS-GUARD	Vandal-resistant Wireless Sensor Guard for surface- or pole-mounting
WR-GUARD	Vandal-resistant Wireless Receiver Guard for pedestal mounting

Compatible with:



Waterproof Wire Connector



Smart WaterMark
Recognised as a responsible water-saving tool (WM-CLIK only)