

MINI-CLIK®

This sensor halts scheduled irrigation when it detects a preset level of rainfall to prevent water waste.

KEY BENEFITS

- Shuts off irrigation automatically when the sensor detects rainfall from 1/8" to 3/4"
- Debris-tolerant for reliable operation and no unnecessary shutdowns
- Wireless sensor kit simplifies installation*
- Quick Response® Technology triggers faster system shutdown for plant protection*
- Built-in freeze sensing halts system operation at 37°F to protect plants and keep roads and walkways ice-free*
- Maintenance-free design with integrated battery for wireless models
- Compatible with most normally open or normally closed irrigation controllers

OPERATING SPECIFICATIONS

- Quick Response Technology* (when enabled):
 - Time to turn off irrigation system: approximately 2 to 5 minutes
 - Time to reset: approximately 4 hours under dry, sunny conditions
 - Time to reset when fully wet: approximately 3 days under dry, sunny conditions
- All models switch rating (24 VAC): 3 A
- Wired models include 25' of 20 AWG sheathed, UL-approved wire
- Wireless model operating frequency: 433 MHz
- Wireless model range is 800' line of sight from sensor to receiver
- Multiple wireless receivers can be operated from a single wireless sensor
- Approvals: UL, cUL, FCC, CE, UKCA, RCM
- Warranty period: 5 years

USER-INSTALLED OPTIONS

- Optional Gutter Mount for wired models (included with WM-CLIK)
- Vandal-resistant Wireless Sensor Guard for flat surfaces or pole mounting (order sensor separately)
- Vandal-resistant Wireless Receiver Guard for pedestal mounting (order receiver separately)

*Wireless Mini-Clik Sensor only

MINI-CLIK	
Model	Description
MINI-CLIK	Wired Mini-Clik Sensor
MINI-CLIK-NO	Wired Mini-Clik Sensor, normally open switch
MINI-CLIK-C	Wired Mini-Clik Sensor, conduit mount
SG-MC	Wired Mini-Clik Sensor in a stainless steel sensor enclosure
WM-CLIK	Wireless Mini-Clik Sensor, Receiver, and Gutter Mount
WS-GUARD	Vandal-resistant Wireless Sensor Guard for flat surface or pole mounting
WR-GUARD	Vandal-resistant Wireless Receiver Guard for pedestal mounting

Sensor: **Rain, Freeze**



Wired Mini-Clik Sensor
(with mounting arm)
Height: 2"
Length: 6"
Width: 1"



Wired Mini-Clik Sensor
(with stainless steel enclosure)
Height: 5 1/2"
Length: 3"
Width: 4"



Wireless Mini-Clik Sensor
(with mounting arm)
Height: 3"
Length: 8"
Width: 1"



Wireless Receiver
(with wall-mounting hardware)
Height: 4"
Length: 4"
Width: 1 1/2"



Wireless Sensor Guard
(with mounting hardware)
Height: 2 3/4"
Length: 3 3/4"
Width: 1 1/4"



Wireless Receiver Guard
(with mounting hardware)
Height: 5"
Length: 4"
Width: 1 1/4"

Compatible with:



Waterproof Wire Connector