

# PRO-C® & PCC

Number of Stations: **4 - 16, 6 & 12**  
 Type: **Modular & Fixed**

## FEATURES

- Number of stations:
  - Pro-C: 4 - 16
  - PCC: 6 & 12
- Type:
  - Pro-C: Modular
  - PCC: Fixed
- Enclosures: Indoor or outdoor plastic
- Independent irrigation programs: 3
- Independent lighting programs: 3
- Start times per program: 4
- Max. station run time: 6 hours
- ▶ Built in Solar Sync
- ▶ Easy Retrieve™ memory
- ▶ QuickCheck™
- ▶ Automatic short circuit protection
- ▶ Seasonal Adjustment: Global or automatic updates with Solar Sync
- ▶ Delay between stations
- ▶ Sensor programmability
- ▶ Non-Water Days
- Solar Sync® Delay feature allows adjustments to be postponed for up to 99 days
- Cycle and Soak feature built in: reduces runoff
- Added knockouts for additional flexibility
- Non-volatile memory
- Rain sensor bypass
- One touch manual start and advance
- Warranty period: 2 years



**Plastic Indoor**  
 Height: 8.25"  
 Width: 9.5"  
 Depth: 3.75"



**Plastic Outdoor**  
 Height: 9"  
 Width: 10"  
 Depth: 4.5"



**PCM-300 and PCM-900 Expansion Modules**  
 These modules are compatible with the new Pro-C 400 series.

## ELECTRICAL SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC (international model)
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.28 A
- Sensor inputs: 1
- Operating temperature: 0° F to 140° F

## APPROVALS

- CE, UL, cUL, C-tick, FCC
- ▶ = *Advanced Feature descriptions on page 88*

| PRO-C SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4 |                                  |    |             |         |                                      |         |  |
|--|----------------------------------|----|-------------|---------|--------------------------------------|---------|--|
| 1  | Models                           | 2  | Transformer | 3       | Indoor/Outdoor                       | 4       | Options  |
| PC-4   | 4-station base module controller | 00 | 120 VAC     | (blank) | Outdoor Model (internal transformer) | (blank) | No option  |
| PCC-6  | 6-Station                        | 01 | 230 VAC     | i       | Indoor Model (plug-in transformer)   | E       | 230 VAC with European Connections  |
| PCC-12   | 12-Station                       |    |             |         |                                      | A       | 230 VAC with Australian Connections (outdoor models have internal transformer with cord) |

**Examples:**

- PC-400** = Modular 4-station outdoor base unit, internal 120 VAC transformer, and plastic cabinet
- PCC-601i - E** = Fixed 6-station indoor controller, plug-in 230 VAC transformer with European connections, and plastic cabinet
- PCC-1200** = Fixed 12-station outdoor controller, Internal 120 VAC transformer, and plastic cabinet

| PC-SERIES STATION EXPANSION |  |
|-----------------------------|--|
| Modules                     | Description  |
| <b>PCM-300</b>              | 3-station plug-in module: Use to increase station count from 4 to 7, 7 to 10, and 10 to 13 |
| <b>PCM-900</b>              | 9-station plug-in module: Use to increase station count from 7 to 16                       |