

ROAM REMOTE

Enable convenient controller management from a distance with this handheld wireless remote.

KEY BENEFITS

- Compatibility with Hunter X-Core®, X2™, Pro-C®, HPC, ICC2, HCC, ACC2, and legacy ACC2 and I-Core® Controllers to enable remote management for projects of any size
- Manually start individual stations or programs for quick maintenance checks and troubleshooting
- 128 programmable addresses available prevents cross-communication between multiple remotes within close proximity of each other
- Programmable run times from 1 to 90 minutes, which will not overwrite regular automatic programming
- Manual operation up to 240 stations provides flexibility for larger projects

OPERATING SPECIFICATIONS

- Range: 1,000' from transmitter to receiver
- Transmitter power source: 4 x AAA batteries included
- Receiver power source: 24 VAC, 0.010 A
- System operating frequency: 433 MHz
- SmartPort® installation: maximum 50' from controller
- FCC and CE approved for use in the United States and internationally
- Warranty period: 2 years



ROAM Transmitter and Receiver

Height: 7"
Width: 2¼"
Depth: 1¼"



SmartPort

Hunter remotes require the installation of a SmartPort Wiring Harness. The SmartPort is a connector that is wired to the terminals on the controller, and allows quick connection to any Hunter receiver.



Wall-Mount Bracket for SmartPort

P/N 258200

ROAM

Model	Description
ROAM-KIT	Transmitter, receiver, SmartPort Wiring Harness, and 4 AAA batteries
ROAM-TR	Transmitter unit and 4 AAA batteries included
ROAM-R	Receiver unit

USER-INSTALLED OPTIONS

Model	Description
ROAM-WH	SmartPort Wiring Harness (length: 6')
ROAM-SCWH	Shielded SmartPort Wiring Harness (length: 25')
258200	Wall-mount bracket for SmartPort