

ROAM XL REMOTE

Add professional, license-free remote control to projects of any size with this long-range remote.

KEY BENEFITS

- Compatibility with Hunter X-Core®, X2™, Pro-C®, HPC, ICC2, HCC, ACC2, and legacy ACC2 and I-Core® Controllers to enable remote management for projects of any size
- Manually start individual stations or programs for quick maintenance checks and troubleshooting
- 128 programmable addresses available prevents cross-communication between multiple remotes within close proximity of each other
- Programmable run times from 1 to 90 minutes, which will not overwrite regular automatic programming
- Manual operation up to 240 stations provides flexibility for larger projects
- Rugged and water-resistant transmitter includes a large LCD display with simple push-button operation and a battery-life indicator

OPERATING SPECIFICATIONS

- Range: 2 miles (line of sight) from transmitter to receiver
- Transmitter power source: 4 x AAA batteries included
- Receiver power source: 24 VAC, 0.010 A
- System operating frequency: 27 MHz
- SmartPort® installation: maximum 50' from controller
- FCC approved (not available in EU and some other countries, check local regulations)
- Warranty period: 3 years



ROAM XL Transmitter and Receiver

(without antenna)
Height: 6¼"
Width: 3"
Depth: 1¼"



SmartPort

Hunter remotes require the installation of a SmartPort Wiring Harness. The SmartPort is a connector that is wired to the terminals on the controller, and allows quick connection to any Hunter receiver.



Wall-Mount Bracket for SmartPort

P/N 258200

| ROAM XL | |
|------------|---|
| Model | Description |
| ROAMXL-KIT | Transmitter, receiver, SmartPort Wiring Harness, 4 AAA batteries and plastic carrying case included |
| ROAMXL-TR | Handheld transmitter and 4 AAA batteries included |
| ROAMXL-R | Receiver unit (SmartPort Wiring Harness included) |

| USER-INSTALLED OPTIONS | |
|------------------------|--|
| Model | Description |
| 258200 | Wall-mount bracket for SmartPort |
| ROAM-WH | SmartPort Wiring Harness (length: 6') |
| ROAM-SCWH | Shielded SmartPort Wiring Harness (length: 25') |
| ROAMXL-EXT | ROAM XL Antenna Extension Kit (25' cable and mounting hardware included) |