

RZWS-E

Cultivate stronger, deeper roots by delivering water and oxygen directly to the root zone of trees and shrubs.

KEY BENEFITS

- Top serviceable cap design
- Pressure-compensating bubbler for accurate water flow
- Built-in Hunter Swing Joint for direct installation to ½" PVC fitting
- Pre-assembled for fast installation

OPERATING SPECIFICATIONS

- Bubbler flow rates: 0.9 l/min or 1.9 l/min
- Recommended pressure range: 1.0 to 4.8 bar; 100 to 480 kPa
- Warranty period: 2 years

RZWS-E - SPECIFICATION BUILDER: Order 1 + 2

1 Model	2 Bubbler Flow Rate
RZWS-E-18 = 45 cm Root Zone Watering System	25 = 0.9 l/min
RZWS-E-36 = 90 cm Root Zone Watering System	50 = 1.9 l/min

Examples:

- RZWS-E-18-50 = 45 cm Root Zone Watering System, 1.9 l/min bubbler
- RZWS-E-36-25 = 90 cm Root Zone Watering System, 0.9 l/min bubbler



RZWS-E-18
Diameter: 7.6 cm
Length: 45 cm

RZWS-E-36
Diameter: 7.6 cm
Length: 90 cm

MICRO

RZB

This accessory for small trees and shrubs assists in delivering water to roots.

KEY BENEFITS

- Solid mesh tube with perforated top to complement overhead or drip irrigation systems
- Allows oxygen and natural precipitation to reach the root zone
- Easy installation that directs overhead and drip irrigation to the root zone
- Warranty period: 1 year



RZB
Diameter: 5 cm
Length: 23 cm

