

IRRIGATION LEGEND

PRODUCT DESCRIPTION

- HUNTER I-35-06-SS-XX NOZZLE AS SHOWN HUNTER I-35-06-SS-XX NOZZLE AS SHOWN
- HUNTER ICV/IBV ELECTRIC CONTROL VALVE SIZE AS SHOWN NOZZLE PERFORMANCE: #13 @ 40 PSI - 12.4 GPM 53' RADIUS
- WATER METER MINIMUM SIZE @ 50 GPM IS 1.5" HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR

HUNTER IC-600 SOLID STATE METAL CABINET CONTROLLER HUNTER HQ-44-XX-AW QUICK COUPLER VALVE (OPTIONAL)

- MAINLINE PIPE BACKFLOW PREVENTER SIZED TO SYSTEM GPM
- LATERAL PIPE

SLEEVING ISOLATION VALVE LINE SIZED

HUNTER FLOW SENSOR IN LINE SIZED FLOW CLIK TEE "FCT"

IRRIGATION NOTES

- SPRINKLER LOCATIONS ARE TO SCALE
 PIPE LOCATIONS ARE DIAGRAMMATIC
 ALL SPRINKLERS TO BE INSTALLED ON 1" SCH 80 SWING JOINTS
 ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS

RECOMMENDATIONS

- 5. MAINLINE DEPTH TO BE NO LESS THAN 18"
 6. LATERAL DEPTH TO BE NO LESS THAN 16"
 7. ELECTRIC CONTROL VALVES TO BE COVERED WITH 12" VALVE 8. LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
- 10. QCV TO BE LOCATED IN 10" VALVE BOX 11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
- 12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE,
- FEDERAL CODES

 13. REFER TO HUNTER INSTALLATION DETAILS

 14. REFER TO HUNTER CATALOG FOR PERFORMANCE SPECIFICAT

 15. ADD HUNTER "FS" FOR DIRTY WATER VALVE

 16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE

SNO

WATER REQUIREMENT

-AT FIELD ELEVATION -WITHIN 100' OF FIELD -DOWNSTREAM OF BACKFLOW IS 50 GPM @ 45 PSI

VALVE ID GUIDE

STATION NUMBER

.50"/hr PRECIPITATION RATE

<u>ا</u>2

VALVE SIZE

SYSTEM PERFO

ZONE SIZE FLOW PR A1 1.5" 50 1.83" A2 1.5" 25 .91" DU SC (10% WINDOW) 77 1.5 77 1.5

RMANCE DATA

Hunter Industries 1940 Diamond Street San Marcos, California 92078 1-800-319-4796 www.HunterIndustries.com

CROQUET COURT

I-35LP DESIGN



SHEET 유 1

for estimating purposes and offers no indemnity, plan. Because of the many variables of every system ation designer be consulted.

SpecPro Technical Assistance