

ZONE A1 A2 A3 A4 A6

273 | I/min 1.5" VALVE SIZE 19.0 PRECIPITATION RATE mm/hr STATION NUMBER

VALVE ID GUIDE

WATER REQUIREMENT

-FIELD ELEVATION
-WITHIN 30m OF FIELD
-DOWNSTREAM OF
BACKFLOW WATER REQUIREMENT AT

IS 343 I/min @ 6.42 Bars

SHEET 유

MULTI-PURPOSE FIELD

I-35 FIVE ROW DESIGN

IRRIGATION LEGEND PRODUCT DESCRIPTION

HUNTER I-35-06-SS-B-XX,
 NOZZLE PERFORMANCE:

#18 @ 3.0 Bars - 24 I/min 13.1m RADIUS

HUNTER ICV/IBV ELECTRIC CONTROL VALVE
HUNTER HQ-44-XX-AW QUICK COUPLER VALVE
HUNTER G-600-M SOLID STATE METAL CABINET CONTROLLER
HUNTER SOLAR SYNC-SEN ON SITE WEATHER SENSOR
WATER METER MINIMUM SIZE @ 343 l/min IS 63mm
BACKFLOW PREVENTER SIZED TO SYSTEM l/min

MAINLINE PIPE LATERAL PIPE

8

ISOLATION VALVE LINE SIZED

SLEEVING

IRRIGATION NOTES

SPRINKLER LOCATIONS ARE TO SCALE

PIPE LOCATIONS ARE DIAGRAMMATIC

3. ALL SPRINKLERS TO BE INSTALLED ON 32mm SCH 80 SWING JOINTS

ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURER RECOMMENDATIONS

MAINLINE DEPTH TO BE NO LESS THAN 460mm
 LATERAL DEPTH TO BE NO LESS THAN 410mm
 ELECTRIC CONTROL VALVES TO BE COVERED WITH 12"

VALVE BOX

8. LOCATE VALVES/OCV'S OUT OF HIGH TRAFFIC AREAS
9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
10. QCV TO BE LOCATED IN 10" VALVE BOX
11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM
12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE,

13. REFER TO HUNTER INSTALLATION DETAILS
14. REFER TO HUNTER CATALOG FOR PERFORMANCE

FEDERAL CODES

15. ADD HUNTER "FS" FOR DIRTY WATER VALVE
16. ADD HUNTER "AS" FOR PRESSURE REGULATED VALVE SPECIFICATIONS

FLOW m/hr l/min 20.6 343 20.6 343 20.6 343 20.6 343 20.6 343 20.6 343 20.6 343 20.6 343 SC

SYSTEM PERFORMANCE DATA 222222 <u>S</u>

79 79 79 79 79 $\begin{smallmatrix} 1 & 1 & 1 & 1 & 1 & 1 \\ \omega & \omega & \omega & \omega & \omega & \omega \\ \end{smallmatrix}$

Hunter Industries 1940 Diamond Street San Marcos, California 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com