

IRRIGATION LEGEND

PRODUCT DESCRIPTION
HUNTER I-25-04-SS-B-XXI-25-06-SS-B-XX, NOZZLE AS SHOWN
HUNTER I-25-04-SS-B-XXI-25-06-SS-B-XX, NOZZLE AS SHOWN

NOZZLE PERFORMANCE:

#8 @ 5.0 Bars - 37.8 I/min 15.5m RADIUS #15 @ 5.5 Bars - 61.5 I/min 17.7m RADIUS #15 @ 5.5 Bars - 68.5 I/min 19.2m RADIUS

HUNTER ICV/IBV ELECTRIC CONTROL VALVE SIZE AS SHOWN HUNTER HQ-44-XX-AW QUICK COUPLER VALVE (OPTIONAL) HUNTER IC-1200-M SOLID STATE METAL CALVE (ONTROLLER HUNTER SOLAR-SYNC-SEN ON SITE WEATHER SENSOR WATER METER MINIMUM SIZE @ 274 l/min IS 63mm BACKFLOW PREVENTER SIZED TO SYSTEM l/min

MAINLINE PIPE LATERAL PIPE SLEEVING

8

ISOLATION VALVE LINE SIZED

IRRIGATION NOTES

- 1. SPRINKLER LOCATIONS ARE TO SCALE
- PIPE LOCATIONS ARE DIAGRAMMATIC
- 3. ALL SPRINKLERS TO BE INSTALLED ON 32mm SCH 80 SWING JOINTS
- 4. ALL COMPONENTS TO BE INSTALLED AS PER MANUFACTURERS RECOMMENDATIONS
- MAINLINE DEPTH TO BE NO LESS THAN 460mm

5 7

- ELECTRIC CONTROL VALVES TO BE COVERED WITH LATERAL DEPTH TO BE NO LESS THAN 410mm 12" VALVE BOX
- 8. LOCATE VALVES/QCV'S OUT OF HIGH TRAFFIC AREAS 9. WIRE SPLICE CONNECTIONS TO BE WATERPROOF
- 11. ALL SLEEVES TO BE 2X PIPE RUN THROUGH THEM 10. QCV TO BE LOCATED IN 10" VALVE BOX
- 12. INSTALL ALL COMPONENTS AS PER LOCAL, STATE, FEDERAL CODES
- 14. REFER TO HUNTER CATALOG FOR PERFORMANCE 13. REFER TO HUNTER INSTALLATION DETAILS

SPECIFICATIONS

15. ADD HUNTER "FS" FOR DIRTY WATER VALVE

SPRINKLER PERMFORMANCE DATA SIZE FLOW

VALVE SIZE

PRECIPITATION RATE mm/h STATION NUMBER

VALVE ID GUIDE

SOFTBALL FIELD

I-25 FOUR ROW DESIGN

SHEET

유

Hunter Industries offers this plan as a general guide for estimating purposes and offers no Indemnity, expressed or implied, for projects installed from this plan. Because of the many variables of every system and of every site we recommend that a qualified ritgation designer be consulted

Hunter Industries 1940 Diamond Street San Marcos, California 92078 SpecPro Technical Assistance 1-800-319-4796 www.HunterIndustries.com