

HC

Number of Stations: **6, 12**
Expands up to 36 stations
Wi-Fi Enabled

FEATURES

- New style full-functioning controller with touchscreen
- Wi-Fi enabled for simple connection to the internet
- 6 and 12 station standard controllers
- 12 station expansion module allows for expansion to 36 stations
- 2 sensor ports
- Warranty 2 years
- ▶ Touchscreen Interface
- ▶ Wi-Fi Controller
- ▶ Predictive Watering Adjustments
- ▶ Flow Meter Detection And Alerts
- ▶ Wiring Detection And Alerts
- ▶ Advanced Sensor Ports



Plastic Indoor

Height: 15.2 cm
 Width: 17.8 cm
 Depth: 3.3 cm



Flow Meter - 3/4" BSP thread

Height: 13 cm
 Width: 8 cm
 Depth: 8 cm

Flow Meter - 1" (25 mm) BSP thread

Height: 16 cm
 Width: 8 cm
 Depth: 8 cm



Compatible with HydraWise software

ELECTRICAL SPECIFICATIONS

- Transformer input: 120 VAC or 230 VAC (international model)
- Transformer output (24 VAC): 1 A
- Station output (24 VAC): 0.56 A
- Pump/master valve (24 VAC): 0.28 A
- Sensor inputs: 2
- Operating temperature: 0°F to 140°F

APPROVALS

- CE, C-tick, FCC
- ▶ = *Advanced Feature descriptions on page 99*
- * Hydrawise software information on page 120

HC - OPTIONS

Models	Description
HC-1200M	12 station expansion module
HC-075-FLOW-B	Flow meter with 3/4" BSP thread
HC-100-FLOW-B	Flow meter with 1" (25 mm) BSP thread

HC - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Models	2 Transformer	3 Indoor/Outdoor	4 Options
HC-6 = 6 station controller with Wi-Fi connection	00 = 120 VAC	i = Indoor model	(Blank) = No option
HC-12 = 12 station indoor controller with Wi-Fi connection	01 = 230 VAC		E = 230 VAC with European connections A = 230 VAC with Australian connections <i>(outdoor model has internal transformer with cord)</i>

Examples:

HC-600i-A = 6-Station 230 VAC indoor plastic controller, and with Australian cord
HC-1200i-E = 12-Station 120 VAC indoor plastic controller, and with European cord

CONTROLLERS