

ST-90-B

The ST-90-B synthetic turf rotor is designed for installation in natural turf adjacent to the playing surface — the perfect solution for small and midsize fields.

KEY BENEFITS

- Arc setting: 40° to 360°
- QuickCheck™ arc mechanism
- Through-the-top arc adjustment
- Water-lubricated gear drive
- Factory-installed rubber logo cap
- Nozzle trajectory: 22.5°

OPERATING SPECIFICATIONS

- Radius: 31.4 m to 36.6 m
- Flow: 16.9 to 20.9 m³/hr; 282 to 348 l/min
- Operating pressure range: 6.9 to 8.3 bar; 690 to 830 kPa
- Precipitation rate: 35 mm/hr approximately
- Warranty period: 5 years for component parts

USER-INSTALLED OPTIONS

- Rubber cover kit ST-90: P/N 234200SP

ST ROTOR	
Model	Description
ST-90-B-XX	8 cm pop-up, jar-top cap, adjustable arc, plastic riser, and BSP inlet threads, #73 or #83 preinstalled nozzle



ST-90-B*
 Overall height: 29 cm
 Pop-up height: 8 cm
 Diameter: 14 cm
 Inlet size: 1½" (40 mm) BSP

* Not for use with the ST Vault

ST-90-B NOZZLE PERFORMANCE DATA

Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
73 ●	7.0	700	31.4	16.9	282	34.3	39.6
	7.5	750	33.2	17.5	291	31.7	36.6
	8.0	800	35.1	18.1	301	29.4	34.0
83 ●	7.0	700	34.1	19.1	319	32.8	37.9
	7.5	750	35.4	20.0	333	32.0	37.0
	8.0	800	36.6	20.9	348	31.2	36.1

Notes:

All precipitation rates calculated for 180° operation.
 For precipitation rate of a 360° sprinkler, divide by 2.

Requires minimum 7.0 bar; 700 kPa dynamic pressure supplied to swing joint inlet.

HIGH-FLOW SWING JOINTS

These durable swing joints are easy to position and ensure correct rotor installation height.

KEY BENEFITS

- Heavy-duty, high-flow swing joints with O-ring seals
- HSJ-4 for high-flow I-90 and ST-90 rotors with 2" (50 mm) inlets

High-Flow Swing Joints

HSJ-4 = 50 mm model
 HSJ-5 = 80 mm model



HSJ HIGH-FLOW SWING JOINT - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Inlet Type (from pipe fitting)	3 Outlet Type (to sprinkler inlet)	4 Outlet Style	5 Lay Length
HSJ-4 = 50 mm heavy-duty swing joint	6 = 2" (50 mm) male BSP, horizontal side connection	D = 1½" (40 mm) male BSP	2 = Single top-out	12 = 12" (30 cm) lay arm

Examples:

HSJ-4-6D-212 = HSJ 50 mm heavy-duty swing joint, 50 mm male BSP horizontal side connection to piping, 40 mm male BSP outlet to sprinkler, single top-out, and 30 cm lay arm