

## Eco-Rotator

This compact sprinkler offers maximum efficiency, flexibility, and performance.

### ÖNEMLI AVANTAJLARI

- Automatic matched precipitation for simplified irrigation design and flexibility
- High distribution uniformity for a healthy landscape and maximum water efficiency
- Double-pop feature protects the nozzle from external debris
- Large inlet filter screen protects the nozzle from internal debris in the system
- Heavy-duty spring for consistent riser retraction

### Operating Specifications

- Low precipitation rate
- Radius range: 1.8 to 9.1 m
- Operational pressure range: 1.7 to 3.8 bar; 170 to 380 kPa
- Recommended operating pressure: 2.8 bar; 280 kPa
- Warranty period: 2 years





### User-Installed Option

- Drain Check Valve: 10 cm model (up to 2 m of elevation) P/N: 462237SP







### MP1000

**Atış Mesafesi:** 2,5 - 4,6 m  
**Ayarlanabilir Açı ve Tam Daire**  
**Bordo:** 90° - 210°  
**Koyu Yeşil:** 360°

| Açı  | Basınç |     | Atış Mesafesi | Debi |                    | Yağmurlama mm/sa |     |
|--|--------|-----|---------------|------|--------------------|------------------|-----|
|  | bar    | kPa |               | m    | m <sup>3</sup> /sa | l/dk             | ■   |
| 90°<br>   | 1,7    | 170 | ...           | ...  | ...                | ...              | ... |
|  | 2,0    | 200 | 3,7           | 0,04 | 0,61               | 11               | 12  |
|  | 2,5    | 250 | 4,0           | 0,04 | 0,68               | 10               | 12  |
|  | 2,8    | 280 | 4,1           | 0,04 | 0,70               | 10               | 11  |
|  | 3,0    | 300 | 4,3           | 0,04 | 0,73               | 10               | 11  |
|  | 3,5    | 350 | 4,4           | 0,05 | 0,78               | 10               | 11  |
|  | 3,8    | 380 | 4,6           | 0,05 | 0,81               | 9                | 11  |
| 180°<br>  | 1,7    | 170 | ...           | ...  | ...                | ...              | ... |
|  | 2,0    | 200 | 3,7           | 0,07 | 1,20               | 11               | 12  |
|  | 2,5    | 250 | 4,0           | 0,08 | 1,35               | 10               | 12  |
|  | 2,8    | 280 | 4,1           | 0,08 | 1,40               | 10               | 11  |
|  | 3,0    | 300 | 4,3           | 0,09 | 1,46               | 10               | 11  |
|  | 3,5    | 350 | 4,4           | 0,09 | 1,56               | 10               | 11  |
|  | 3,8    | 380 | 4,6           | 0,10 | 1,62               | 9                | 11  |
| 210°<br>  | 1,7    | 170 | ...           | ...  | ...                | ...              | ... |
|  | 2,0    | 200 | 3,7           | 0,09 | 1,41               | 11               | 13  |
|  | 2,5    | 250 | 4,0           | 0,10 | 1,58               | 10               | 12  |
|  | 2,8    | 280 | 4,1           | 0,10 | 1,63               | 10               | 11  |
|  | 3,0    | 300 | 4,3           | 0,10 | 1,71               | 10               | 11  |
|  | 3,5    | 350 | 4,4           | 0,11 | 1,82               | 10               | 11  |
|  | 3,8    | 380 | 4,6           | 0,11 | 1,89               | 9                | 11  |
| 360°<br> | 1,7    | 170 | ...           | ...  | ...                | ...              | ... |
|  | 2,0    | 200 | 3,5           | 0,14 | 2,40               | 12               | 14  |
|  | 2,5    | 250 | 4,0           | 0,16 | 2,69               | 10               | 12  |
|  | 2,8    | 280 | 4,1           | 0,17 | 2,81               | 10               | 12  |
|  | 3,0    | 300 | 4,3           | 0,18 | 2,94               | 10               | 11  |
|  | 3,5    | 350 | 4,4           | 0,19 | 3,17               | 10               | 11  |
|  | 3,8    | 380 | 4,5           | 0,20 | 3,25               | 10               | 11  |





## MP2000

**Atış Mesafesi:** 4 - 6,4 m  
Ayarlanabilir Açı ve Tam Daire  
**Siyah:** 90° - 210°  
**Kırmızı:** 360°

| Açı  | Basınç |     | Atış Mesafesi | Debi |                    | Yağmurlama mm/sa |    |
|--|--------|-----|---------------|------|--------------------|------------------|----|
|  | bar    | kPa |               | m    | m <sup>3</sup> /sa | l/dk             | ■  |
| 90°<br>   | 1,7    | 170 | 5,2           | 0,07 | 1,18               | 11               | 12 |
|  | 2,0    | 200 | 5,5           | 0,07 | 1,23               | 10               | 11 |
|  | 2,5    | 250 | 5,8           | 0,09 | 1,43               | 10               | 12 |
|  | 2,8    | 280 | 6,1           | 0,09 | 1,52               | 10               | 11 |
|  | 3,0    | 300 | 6,4           | 0,09 | 1,57               | 9                | 11 |
|  | 3,5    | 350 | 6,7           | 0,10 | 1,68               | 9                | 10 |
|  | 3,8    | 380 | 6,7           | 0,11 | 1,77               | 9                | 11 |
| 180°<br>  | 1,7    | 170 | 4,9           | 0,13 | 2,22               | 11               | 12 |
|  | 2,0    | 200 | 5,2           | 0,14 | 2,35               | 11               | 12 |
|  | 2,5    | 250 | 5,5           | 0,16 | 2,67               | 11               | 12 |
|  | 2,8    | 280 | 5,8           | 0,17 | 2,80               | 10               | 12 |
|  | 3,0    | 300 | 6,1           | 0,17 | 2,90               | 10               | 11 |
|  | 3,5    | 350 | 6,4           | 0,19 | 3,15               | 9                | 10 |
|  | 3,8    | 380 | 6,4           | 0,19 | 3,22               | 9                | 11 |
| 210°<br>  | 1,7    | 170 | 4,9           | 0,16 | 2,58               | 11               | 12 |
|  | 2,0    | 200 | 5,2           | 0,17 | 2,75               | 11               | 13 |
|  | 2,5    | 250 | 5,5           | 0,19 | 3,08               | 10               | 12 |
|  | 2,8    | 280 | 5,8           | 0,20 | 3,25               | 10               | 12 |
|  | 3,0    | 300 | 6,1           | 0,21 | 3,42               | 10               | 11 |
|  | 3,5    | 350 | 6,4           | 0,22 | 3,70               | 9                | 10 |
|  | 3,8    | 380 | 6,4           | 0,23 | 3,80               | 10               | 11 |
| 360°<br> | 1,7    | 170 | 4,9           | 0,27 | 4,42               | 11               | 12 |
|  | 2,0    | 200 | 5,2           | 0,28 | 4,72               | 11               | 13 |
|  | 2,5    | 250 | 5,5           | 0,32 | 5,28               | 10               | 12 |
|  | 2,8    | 280 | 5,8           | 0,33 | 5,55               | 10               | 12 |
|  | 3,0    | 300 | 6,1           | 0,35 | 5,80               | 10               | 11 |
|  | 3,5    | 350 | 6,4           | 0,37 | 6,25               | 9                | 10 |
|  | 3,8    | 380 | 6,4           | 0,38 | 6,40               | 9                | 10 |

#### MP3000

**Atış Mesafesi:** 6,7 - 9,1 m  
Ayarlanabilir Açı ve Tam Daire  
**Mavi:** 90° - 210°  
**Gri:** 360°

| Açı   | Basınç |     |  | Atış Mesafesi | Debi |                    | Yağmurlama mm/sa |    |
|---|--------|-----|--|---------------|------|--------------------|------------------|----|
|   | bar    | kPa |  |               | m    | m <sup>3</sup> /sa | l/dk             | ■  |
| 90°<br>    | 1,7    | 170 |  | 7,6           | 0,16 | 2,63               | 11               | 13 |
|   | 2,0    | 200 |  | 8,2           | 0,17 | 2,77               | 10               | 11 |
|   | 2,5    | 250 |  | 8,5           | 0,19 | 3,08               | 10               | 12 |
|   | 2,8    | 280 |  | 9,1           | 0,20 | 3,25               | 9                | 11 |
|   | 3,0    | 300 |  | 9,1           | 0,20 | 3,38               | 10               | 11 |
|   | 3,5    | 350 |  | 9,1           | 0,22 | 3,67               | 11               | 12 |
|   | 3,8    | 380 |  | 9,1           | 0,23 | 3,80               | 11               | 13 |
| 180°<br>   | 1,7    | 170 |  | 7,6           | 0,32 | 5,48               | 11               | 13 |
|   | 2,0    | 200 |  | 8,2           | 0,35 | 5,88               | 10               | 12 |
|   | 2,5    | 250 |  | 8,5           | 0,40 | 6,55               | 11               | 12 |
|   | 2,8    | 280 |  | 9,1           | 0,41 | 6,88               | 10               | 11 |
|   | 3,0    | 300 |  | 9,1           | 0,43 | 7,18               | 10               | 12 |
|   | 3,5    | 350 |  | 9,1           | 0,47 | 7,77               | 11               | 13 |
|   | 3,8    | 380 |  | 9,1           | 0,45 | 8,02               | 12               | 13 |
| 210°<br>   | 1,7    | 170 |  | 7,6           | 0,38 | 6,40               | 11               | 13 |
|   | 2,0    | 200 |  | 8,2           | 0,41 | 6,85               | 10               | 12 |
|   | 2,5    | 250 |  | 8,5           | 0,46 | 7,65               | 11               | 12 |
|   | 2,8    | 280 |  | 9,1           | 0,48 | 8,02               | 10               | 11 |
|   | 3,0    | 300 |  | 9,1           | 0,50 | 8,37               | 10               | 12 |
|   | 3,5    | 350 |  | 9,1           | 0,54 | 9,03               | 11               | 13 |
|   | 3,8    | 380 |  | 9,1           | 0,56 | 9,37               | 12               | 13 |
| 360°<br> | 1,7    | 170 |  | 7,6           | 0,66 | 10,98              | 11               | 13 |
|   | 2,0    | 200 |  | 8,2           | 0,70 | 11,72              | 10               | 12 |
|   | 2,5    | 250 |  | 8,5           | 0,79 | 13,10              | 11               | 12 |
|   | 2,8    | 280 |  | 9,1           | 0,83 | 13,75              | 10               | 11 |
|   | 3,0    | 300 |  | 9,1           | 0,87 | 14,37              | 10               | 12 |
|   | 3,5    | 350 |  | 9,1           | 0,93 | 15,52              | 11               | 13 |
|   | 3,8    | 380 |  | 9,1           | 0,96 | 16,07              | 12               | 13 |

**Koyu** = Önerilen basınç

Copyright © 2024 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://hunterirrigation.com/tr/irrigation-product/mp-rotator/eco-rotator>  
122324